




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H05B 39/00	A1	(11) International Publication Number: WO 97/34448 (43) International Publication Date: 18 September 1997 (18.09.97)
(21) International Application Number: PCT/US97/03751 (22) International Filing Date: 11 March 1997 (11.03.97) (30) Priority Data: 08/614,712 13 March 1996 (13.03.96) US (71) Applicant: LUTRON ELECTRONICS CO., INC. [US/US]; 7200 Suter Road, Coopersburg, PA 18036-1299 (US). (72) Inventors: BRYDE, Gary, W.; 8 Covington Place, Catasauqua, PA 18032 (US). WOLBERT, Donald, J., III; 101 Alpine Street, Emmaus, PA 18049 (US). HAKKARAINEN, Simo, Pekka; 820 Tioga Avenue, Bethlehem, PA 18018 (US). SPIRA, Joel, S.; 1506 Pleasant View Road, Coopersburg, PA 18036 (US). (74) Agent: LAVORGNA, Gregory, J.; Seidel, Gonda, Lavorgna & Monaco, P.C., Suite 1800, Two Penn Center Plaza, Philadelphia, PA 19102 (US).		(81) Designated States: CA, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: LIGHTING CONTROL WITH WIRELESS REMOTE CONTROL AND PROGRAMMABILITY



(57) Abstract

A remotely controllable and programmable power control unit for controlling and programming the state and power level, including special functions, of one or more electrical devices. The electrical device can be an electric lamp. The system includes a user-actuatable remote transmitter unit and a user-actuatable power control unit adapted to receive control signals from the remote transmitter unit. Both the remote transmitter unit and the power control unit include a power selection actuator for selecting a desired power level between a minimum power level and a maximum power level, and control switches for generating control signals representative of programmed power levels of one or more power scenes and special functions. In response to an input from a user, either directly or remotely, the one or more devices of the one or more power scenes can be controlled between an on or off state, to a desired programmed preset, or to a maximum power level.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

- 1 -

LIGHTING CONTROL WITH WIRELESS REMOTE CONTROL AND PROGRAMMABILITY

FIELD OF THE INVENTION

The present invention relates to a wireless controllable and program-
5 mable power control system for controlling and programming the state and power
intensity level of one or more electrical devices in one or more zones for the creation
of one or more lighting scenes.

BACKGROUND OF THE INVENTION

Lighting control systems comprising switches and dimmers have
10 become increasingly popular, especially for applications where it is desired to
precisely control the level of light intensity in a particular room. In the simplest
type of dimmer controlled lighting systems, a dimmer switch actuator is manipulated
by hand, to control the setting of a variable resistor which in turn controls the
switching of a solid state power control device such as a triac. The switching of
15 the solid state power control device, in turn, varies the voltage input to the lamp
to be dimmed. This type of system, incorporating a dimmer switch, is simple and
easy to construct, but offers limited additional features and flexibility. One feature
this system lacks is the ability to return to a prior or preset light intensity level after
having been adjusted to a subsequent intensity level. Typically, a dimmer switch
20 based system has no ability to memorize or recall prior intensity settings.
Consequently, preset light intensity levels can be reestablished only by trial and error
in manipulating the variable resistor of the dimmer.

Other lighting control systems comprise touch actuator operated
lighting controls which address some of the limitations associated with the manually-
25 operated variable resistor controlled dimmer switch previously described. In one

- 2 -

example of a touch actuator operated control system, the lamp is cycled repetitively through a range of intensities, from dim to bright, in response to extended touch inputs. When the desired intensity is reached, the touch input is removed, the cycle will stop, and the level of light intensity is set (preselected) and stored in a memory

5 function that is typically provided by such systems. Typically, a subsequent short touch input will turn the lamp off, and a further short touch input will turn the lamp on at the set intensity level stored in the memory. While this type of device is an improvement over manually-operated dimmer switches, it requires the user to go through the cycle of intensity levels in order to arrive at a different intensity level.

10 In addition, this type of device lacks the ability to return to a set or preset intensity level when the level is changed. A user must go through the cycle again until he or she finds the light intensity level desired. Moreover, this type of device has no ability to perform certain aesthetic effects such as a gradual fade from one light intensity level to another.

15 U.S. Patent 4,649,323 discloses a microcomputer-controlled light control which provides a fade function. The control disclosed in that patent is operated by a pair of non-latching switches which provide inputs to a microcomputer. The microcomputer is programmed to determine whether the switches are tapped or held (i.e., whether they are touched for a transitory duration or for a longer period

20 of time). When a switch is held, the light intensity is either decreased or increased, and release of the switch causes the intensity setting to be entered into a memory. If the control is operating at a static light intensity level, a tap of a switch will cause the light intensity level to fade to a preset level, either off, full on, or an intermediate level. A tap while the light intensity level is fading will cause the fade to be terminated and cause the light intensity level to shift immediately and abruptly to either

25 full on or full off, depending on which switch is tapped. This type of control, however, is not without drawbacks of its own. For example, a single tap by a user is interpreted in either of two very different ways (initiate fade or terminate fade), depending on the state of the control at the time the user applies the tap to a switch.

30 This can be confusing to a user, who may erroneously terminate a fade when it is desired to initiate a fade, and *vice versa*. In addition, it is not possible to reverse a fade by a subsequent tap of the same switch while a fade is in progress. Instead, a tap while the control is fading in one direction will not reverse the direction of the fade but will cause the control to "jump" to either full on or full off. An abrupt

- 3 -

shift from a low intensity level to full on, or from a high intensity to no light at all (full off), can be quite startling to the user and others in the area (and even dangerous, if the user and others are suddenly plunged into darkness).

5 The control disclosed in patent 4,649,323 also lacks a long-duration
fade to off, as do the other prior control designs. In many cases, it is desirable for
a user to be able to have the lights fade out gradually. For example, a user may
wish to turn out bedroom lights before retiring, but still have sufficient light to safely
make his or her way from the control location to the bed before the lights are
completely extinguished. There may also be situations where the night staff of a
10 large building may need to extinguish ambient lights from a central location which
is located some distance away from an exit, and may need a level of illumination
in order to walk safely to the exit. These features would not be possible with the
prior control, which would offer the user either almost immediate darkness or a
constant level of intensity throughout the night, neither of which would be acceptable.

15 Commonly assigned U.S. Patents Nos. 4,575,660, 4,924,151,
5,191,265, 5,248,919, 5,430,356, and 5,463,286, disclose various lighting control
systems in which lamps or groups of lamps, in one or more zones, are varied in
brightness to produce several different scenes of illumination. The level of
brightness of the lamps constituting each lighting group is displayed to the user by
20 either the number of light emitting diodes, LED's illuminated in a linear array of
the LED's, or the position of a potentiometer slider in a linear track.

U.S. Patents Nos. 5,191,265, and 5,463,286 disclose wall mounted
programmable modular control systems for controlling groups of lights in one or
more zones. In these systems, the lights are controlled by a master control wall
25 module, a remote wall unit, and by a remote hand held control unit. The hand held
unit communicates to the master control module by conventional infra-red (IR)
transmission techniques.

The lighting control device in patent 5,248,919 has all of the light
control features needed to effectively and safely control the state and intensity level
30 of one or more lights. However, this device lacks many desirable features such as
wireless remote controllability, programmability, the ability to lock and unlock a
preset function and a delayed off. In many cases, it is desirable for a user to be able
to have one or more lamps fade to a pre-selected intensity level or state, or to fade
to off after a variable delay time. It would be even more useful and desirable to

- 4 -

be able to remotely control and program the preset light intensities of one or more lamps associated with one or more lighting scenes.

Another lighting device known in the art as "Onset Dimmer OS600" is manufactured by Lightolier Controls, Inc. Unlike the present invention, which allows a user to selectively lock and unlock a stored preset light intensity level with an actuator, which also performs other functions, the prior art Lightolier device cannot unlock the preset light intensity when stored. In other words, the Lightolier device can only lock a different preset light intensity into its memory. Further, unlike the present invention, the Lightolier device uses a separate dedicated switch with a separate dedicated actuator in order to lock in a preset light intensity level.

There is thus a need for an improved lighting control system which offers advantages not possible with prior controls while avoiding the drawbacks of the prior controls. The present invention fills that need.

SUMMARY OF THE INVENTION

The present invention is directed to a wireless remotely controllable and programmable power control unit and receiver system having at least one power control unit for controlling and programming the state and power level of one or more electrical devices. When the electrical device is a light source, one or more power control units control the intensity of the one or more light sources in one or more zones for the creation of one or more lighting scenes. The system includes a user-actuatable wireless remote hand held transmitter unit, and at least one power control and receiver unit adapted to receive control signals from the remote transmitter unit. The receiver of the power control unit includes a wide angle infra-red (IR) lens which has a wide field of view in a horizontal plane but a limited field of view in a vertical plane.

One embodiment of the present invention includes a basic user-actuatable wireless remote control unit. The basic wireless remote control unit has a raise/lower type intensity control and a single on/off control. The basic wireless remote control unit sends control signals to one or more receiver units which in turn control one or more light sources in one or more zones. Each receiver unit defines a zone controlling one or more light sources. The basic wireless remote control unit can control one or more receiver units, as a group. This means that the basic remote unit commands all the receiver units to control the lamps connected to then

- 5 -

simultaneously. A unique feature of the basic wireless remote control unit is that the controls mimic controls of the receiver unit. Hence, operating a control on the basic wireless remote control has the same effect as operating the corresponding control on the receiver unit.

5 Another embodiment of the present invention includes an enhanced wireless remote control unit having one or more scene selection switches. In addition to having the features of the basic wireless remote control unit, the enhanced remote unit can send scene control signals to one or more receiver units to control them as a group. In addition, the enhanced wireless remote control unit can program the
10 lighting levels associated with each lighting scene so that a desired preset light level can be established and stored in memory in the receiver unit.

 Yet another embodiment of the present invention includes a second basic or a second enhanced wireless remote control unit having all the features of the previous embodiments in addition to an address selection switch. The address
15 selection switch is used to address and send control signals to one or more receiver units assigned the selected address either individually or as a group. In addition to controlling the receiver units, once they have been assigned address the second enhanced remote unit can be used to assign addresses to individual receiver units.

 In all embodiments of the present invention, the program mode is
20 built into the receiver unit so that it can be programmed remotely by the enhanced wireless remote control units. In the program mode, the user can select and store one or more desired preset light intensity levels for the lights controlled by the receiver unit.

 In all embodiments of the invention, a preset light intensity level can
25 be stored into the receiver unit by three actuations of the on/off switch (locking a preset). When the preset level is stored and locked, the receiver unit will always return to the locked preset level when given an on command, either directly or remotely. The stored preset level can also be cleared by four actuations of the on/off switch (unlocking a preset). If the stored preset level is not locked before an off
30 command, the receiver unit will return to the intensity level to which it was set just prior to the last off command, when the receiver unit is again turned on.

 In the preferred embodiment of the present invention, the basic and enhanced wireless remote control units employ conventional infra-red (IR) signal encoding as a means to transmit control signals to the receiver unit. The encoded

- 6 -

control signals are for commanding such things as a scene select, increase light intensity, decrease light intensity, light on, light off, lights to full, light off after a delay, enter program mode, set preset level, and set address. However it is understood that other encoded signals can be employed. In addition, other transmitting and receiving means such as radio frequency (RF) and lightwave signals can be employed.

In the preferred embodiment of the present invention, the wireless remote control units and the receiver units have at least one scene control or an on/off control, and at least one raise/lower intensity control. The intensity control enables the user to select a desired intensity level between a minimum intensity level and a maximum intensity level. The scene control enables a user to select a preset light intensity level for one or more light sources in one or more zones that define a lighting scene. The on/off control enables a user to fade the light intensity either on or off.

In addition, the on/off control enables a user to activate additional features. These additional features include, but are not limited to, a variable delay to off, and a fade to full and are described in detail below.

An FADE TO OFF response is effected by a single actuation, for example a temporary application of pressure sufficient to open or close a switch once, causing all lights associated with at least one receiver unit to fade, at a first fade rate, from any intensity level to an off state.

A FADE TO PRESET response is effected by a single actuation, causing a light to fade, at a first fade rate, from an off state or any intensity level to a preprogrammed preset intensity level.

A DELAY TO OFF response is effected by a press and hold actuation, i.e., a more than a temporary application of pressure sufficient to open or close a switch, causing a light to fade, at a first fade rate, from any intensity level to an off state after a variable delay. The variable delay is a function of user input and is equal to: $(\text{hold time} - 0.5) \times 20 \text{ seconds}$.

A FADE TO FULL is effected by a double actuation, two temporary applications of pressure sufficient to open or close a switch applied in rapid succession, causing a light to fade, at a second fade rate, from an off state or any intensity level to a maximum intensity level.

- 7 -

In one embodiment of the invention, the intensity selection actuator comprises a rocker switch actuatable between first, second, and third positions. The first position corresponds to an increase in intensity level, and the second position corresponds to a decrease in intensity level. The third is a neutral position.

5 In an alternate embodiment, the intensity selection actuator comprises first and second switches, each actuatable between a first and second position. Actuation of the first switch causes an increase in the desired intensity level and actuation of the second switch causes a decrease in the desired intensity level at specific fade rates.

10 In a preferred embodiment of the receiver unit, a plurality of illuminated intensity indicators are arranged in a sequence representing a range from a minimum to a maximum intensity level. The position of each indicator within the sequence is representative of an intensity level relative to the minimum and maximum intensity levels of the controlled light sources. The sequence may, but need not,
15 be linear. The invention also comprises a first indicator, having a first illumination level, for visually indicating the preset intensity level of a controlled light when the light is on. The preferred embodiment may further comprise a second indicator, having a second illumination level, for visually indicating a preset intensity level of a controlled light when the light is off. The second illumination level is less than
20 the first illumination level when said light is on. The second illumination level is preferably sufficient to enable said indicators to be readily perceived by eye in a darkened environment.

In yet another embodiment of the present invention, the control system preferably includes a microcontroller having changeable software. The
25 microcontroller may include means for storing in a memory digital data representative of the delay times. The microcontroller may also include means for storing in a memory digital data representative of a preset intensity level. Further, the control system may comprise a means for changing or varying the fade rates or delay to off stored in memory. The microcontroller may also include means for distinguishing
30 between a temporary and more than a temporary duration of actuation of a control switch, for the purpose of initiating the fade of a light according to an appropriate fade rate.

- 8 -

In one embodiment of the invention, all fade rates are equal. In an alternate embodiment, each fade rate is different. In still another embodiment, the second fade rate is substantially faster than the first fade rate.

5 In an alternate embodiment of the present invention, the power control unit includes an infrared lens for receiving infrared light signals containing information transmitted from a wireless infrared transmitter.

10 In one aspect of the invention, the lens comprises a planar infrared receiving surface, an infrared output surface, and a flat infrared transmissive body portion therebetween. The output surface of the lens has a shape substantially conforming to an input surface of an infrared detector. The flat body portion of the lens has external side surfaces substantially conforming to an ellipse. The side surfaces are positioned on either side of a longitudinal axis that is defined by the lens. The elliptical side surfaces are shaped to reflect the infrared light that enters the lens input surface. The light reflects off the side surfaces and passes through
15 the body portion to the output surface. The output surface directs the infrared light onto the input surface of the infrared detector. The infrared detector is positioned substantially behind the lens output surface.

In another aspect of the invention, the infrared lens is located on movable number so that the lens output surface is adjacent to an input surface of
20 an infrared detector. The infrared detector is located in a fixed position behind the lens. The movable number and the lens move in a direction that is toward or away from the fixed position of the infrared detector and its input surface.

BRIEF DESCRIPTION OF THE DRAWINGS

25 For the purpose of illustrating the invention, there is shown in the drawings forms which are presently preferred; it being understood, however, that this invention is not limited to the precise arrangements and instrumentalities shown.

FIG. 1 shows a front view of a preferred embodiment of a power control and receiver unit with an infra-red lens in accordance with the present invention.

30 FIG. 2 shows a top view of a preferred embodiment of a hand held basic remote control unit in accordance with the present invention.

FIG. 2A shows a left side view of the basic remote control unit as shown in FIG. 2.

FIG. 2B shows a right side view of the basic remote control unit as shown in FIG. 2.

FIG. 2C shows an end view of the basic remote control unit shown in FIG. 2.

5 FIG. 3 shows a top view of a preferred embodiment of a wireless enhanced transmitter unit in accordance with the present invention.

FIG. 3A shows a right side view of the enhanced transmitter unit as shown in FIG. 3.

10 FIG. 3B shows an end view of the enhanced transmitter unit as shown in FIG. 3.

FIG. 4 shows a top view of an alternate preferred embodiment of a wireless transmitter unit having scene controls in accordance with the present invention.

15 FIG. 4A shows an end view of the wireless transmitter unit having as shown in FIG. 4.

FIG. 5 shows a top view of an alternate embodiment of a preferred wireless enhanced transmitter unit having scene and special function controls and in accordance with the present invention.

20 FIG. 5A shows an end view of the alternate enhanced transmitter unit as shown in FIG. 5.

FIG. 6 shows a functional flow diagram of the operation of the transmitter units.

FIG. 7 shows top plan view of a preferred embodiment of a infrared lens in accordance with the present invention.

25 FIG. 8A illustrates the operation of the infrared lens shown in FIG. 7, when infrared light at an incident ray angle of 0° passes through lens.

FIG. 8B illustrates the operation of the infrared lens shown in FIG. 7, when infrared light at an incident ray angle of 40° passes through lens.

30 FIG. 8C illustrates the operation of the infrared lens shown in FIG. 7, when infrared light at an incident ray angle of 80° passes through lens.

FIG. 9A illustrates the installation of the infrared lens located in a moveable surface, in accordance with the present invention.

FIG. 9B is an isometric illustration of the infrared lens located in a moveable surface and an infrared detector.

- 10 -

FIG. 10 shows a block diagram of the circuitry of the receiver unit shown in FIG. 1.

FIG. 11 shows a block diagram of the circuitry of the basic remote control unit shown in FIG. 2.

5 FIG. 12A shows a block diagram of the circuitry the enhanced remote control unit shown in FIG. 3.

FIG. 12B shows a block diagram of the circuitry of the enhanced remote control unit shown in FIG. 4.

10 FIG. 12C shows a block diagram of the circuitry of the enhanced remote control unit shown in FIG. 5.

FIGS. 13 - 20 show a functional flow diagram of the operation of the receiver unit.

FIG. 21 illustrates delay to off profiles for the power control device shown in FIG. 1.

15

DETAILED DESCRIPTION

Referring now to the drawings, wherein like numerals indicate like elements, there is shown in **FIG. 1** a power control and infra-red receiving control unit **10** embodying a power control device according to the present invention for controlling electric power delivered to at least one electrical device (not shown).

20 The control unit **10** comprises a cover plate **11** and a plurality of control actuators comprising a user actuatable power level selection actuator **12**, a user actuatable control switch actuator **13**, hereinafter referred to as a toggle switch actuator **13**, and an air gap switch actuator **18** which controls an air gap switch (not shown) for removing all electric power to the control unit **10**. The control unit **10** further

25 comprises a power level indicator in the form of a plurality of individual LEDs **14** arranged in a line.

The control unit **10** further comprises an infra-red (IR) receiving lens **70** located in an opening **15** on the toggle switch actuator **13**. The lens **70** captures IR control signals that are transmitted by any one of a number of wireless transmitter units **20**, **30**, **40**, **50**, described below. The structure of infra-red receiving lens **70**

30 will be described in more detail below.

In one aspect of the invention, power control signals are transmitted to the control unit **10** by a wireless hand held user actuatable basic remote control

- 11 -

20 or a wireless hand held user actuatable enhanced remote control 30, 40, 50, depicted in FIGS. 2, 3, 4, and 5, respectively.

5 In another aspect of the invention, the control unit 10 embodies a power control and infra-red receiver circuit 100 shown in Fig. 10, for controlling one or more electrical devices. The control unit 10 is designed to control the electric power delivered to at least one electrical device.

10 Preferably, the electrical device controlled by control unit 10 is an electric lamp or lamps 114, as shown in Fig. 10. The control unit 10 controls the electric power delivered to, and hence the light intensity of, the electric lamp or lamps 114 in known manner by using a phase controlled triac circuit or otherwise.

However, it is to be understood that the electrical device could be a fan, a motor, a relay, etc. In addition, the type of lamp 114 controlled is not limited to an incandescent lamp but could be a low voltage incandescent lamp, a fluorescent lamp, or other type of lamp.

15 The preferred embodiments described below are described in the context of the electrical device being a lamp or lamps 114 and the control unit 10 controlling the intensity of these lamps.

When the electrical device includes at least one lamp, the at least one lamp defines a lighting zone (hereinafter zone.) By incorporating multiple control
20 units 10, multiple zones can be created and controlled. The zones are used to create lighting scenes (hereinafter scenes) by controlling the power level, and therefore the intensity, of the lamps associated with one or more zones, thereby creating a plurality of scenes. Therefore, multiple scenes can be created with one or more power control units 10, which can be controlled by the control unit or the remote transmitters 20,
25 30, 40, 50.

Hereinafter, the terms "actuation" or "actuated" mean either opening, closing, or maintaining closed for a particular period of time, a switch having one or more poles. In the preferred embodiment of the invention the switches are momentary contact switches and actuation is caused by the application of pressure
30 to the switch actuator of sufficient force to either open or close a switch. However, other types of switches could be used.

POWER CONTROL AND RECEIVER UNIT

Referring to **FIG. 1**, the power level selection actuator **12** is actuated by the user to set a desired level of light intensity of the one or more electric lamps controlled by the control unit **10**. The selection actuator **12** further comprises an upper power level selector portion **12a** and a lower power level selector portion **12b**, controlling respective power level selector switches **62a**, **62b** shown in **FIG. 10**.

The upper power level selector portion **12a**, when actuated, causes an increase or "RAISE" in intensity of the lamps controlled by the control unit **10**. Conversely, the lower power level selector portion **12b**, when actuated with control unit **10** in the on state, causes a decrease or "LOWER" in intensity of the lamps controlled by the control unit **10**. In addition, if the lower power level selector portion **12b** is actuated when control unit **10** is in the off state, it can be used to set and store a delay to off time. The longer the lower power level selector **12b** is actuated, the longer the delay time to be set and stored.

The actuation of user actuatable control switch actuator **13** causes control unit **10** to respond in a variety of ways, depending on the precise nature of the actuation of control switch actuator **13** which actuates control switch **63**, *i.e.*, whether it is actuated for a transitory period of time or a longer than transitory period of time, or whether it is actuated for several transitory periods of time in quick succession, and also depending on the state of the control unit **10** prior to the actuation of the control switch actuator **13**.

In the present, an actuation has a transitory duration if the duration of the actuation is less than 0.5 seconds. Two successive actuations of the actuator, in rapid succession (double tap), refers to two transitory actuations that are within 0.5 seconds of each other. Three successive actuations of an actuator, in rapid succession (triple tap), refers to three transitory actuations all within 1.0 second. Four successive actuations of an actuator, in rapid succession (quad tap), refers to four transitory actuations all within 1.5 seconds.

Although these time periods are presently preferred for determining whether a double tap, triple tap, or quad tap actuations has occurred, any short period of time may be employed without departing from the invention. For example, a time period of 1.5 seconds could be used for determining whether a double tap, triple tap, or a quad tap has occurred so that in an alternative embodiment of the invention, if two successive actuations of transitory duration occurred in 1.5 seconds

- 13 -

it would be considered a double tap. The period of time during which multiple successive actuations of transitory duration are looked for is considered to be a short duration of time.

It is also possible to have an actuation of an actuator for more than
5 0.5 seconds, which is considered to be extended in nature and has an extended duration.

The responses to the actuation of the control switch actuator **13** are to increase the light intensity from zero to a preset level (FADE TO PRESET), increase the light intensity to maximum (FADE TO FULL), decrease the light
10 intensity to zero (FADE TO OFF), decrease the light intensity to zero after a delay (DELAY TO OFF), store a preset light level in memory (LOCKED PRESET), and remove a preset light level from memory (DISCONTINUE LOCKED PRESET). These features are executed by means of circuitry associated with the control unit **10** and depicted in a block diagram **100**, shown in **Fig. 10**, described in detail in
15 the flow charts illustrated in **Figs. 13-20**.

A FADE TO PRESET response is effected by a single actuation of transitory duration of the user actuatable control switch actuator **13** when the control unit **10** is in the off state, thereby causing the intensity of the electric lamp **114** to increase at a first fade rate, from zero to a preset intensity level. This can be either
20 a locked preset level or the level at which the lamp was illuminated when the control unit **10** was last in an on state, as will be described in more detail below.

A FADE TO FULL response is effected by a double actuation, i.e., two actuations of transitory duration in rapid succession, of the user actuatable control switch actuator **13** (double tap), thereby causing the intensity of the electric
25 lamp **114** to increase, at a second fade rate, from an off state or any intensity level to a maximum intensity level.

A FADE TO OFF response is effected by a single actuation of transitory duration of the user actuatable control switch actuator **13**, thereby causing the intensity of the electric lamp **114** associated with the control unit **10** to decrease,
30 at a third fade rate, from any intensity level to an off state.

A DELAY TO OFF response is effected by an "extended" actuation, i.e., a more than transitory actuation of the user actuatable control switch actuator **13**, thereby causing the intensity of electric lamp **114** to decrease at the third fade rate, from any intensity level to an off state after a delay time. The duration of the

- 14 -

delay time i.e., how long the delay time lasts from beginning to end, is dependent on the length of time the control switch actuator 13 is actuated. In the preferred embodiment the delay time is linearly proportioned to the length of time the control switch actuator 13 is actuated.

5 Actuations of less than 0.5 sec. are considered to be transitory or of short duration. Actuation of greater than 0.5 sec. cause an increase in the delay time of 10 seconds for each additional 0.5 second that control switch actuator 13 is actuated. Hence, if the control switch actuator 13 is held for two seconds, the delay time would be 30 seconds.

10 A variable fade to off could also be effected by an "extended" actuation of the control switch actuator 13, causing the intensity of electric lamp 114 to decrease from any intensity to off with a variable fade rate. The variable fade rate is dependent on the duration of the actuation. Whether the unit has variable delay or variable fade to off on extended actuation of the control switch actuator 13 is
15 dependent on the programming of the microprocessor 108 shown in Fig. 10.

 A LOCKED PRESET response is effected by a triple actuation, i.e., three actuations of transitory duration in rapid succession of the user actuatable control switch actuator 13 (triple tap). The intensity of the lamp 114 does not change but the intensity level is stored in a memory as a locked preset level, and subsequent
20 changes to the intensity level of the lamp do not affect the locked preset level.

 A DISCONTINUE LOCKED PRESET response is effected by a quadruple actuation, i.e., four actuations of transitory duration in rapid succession of the user actuatable control switch actuator 13 (quadruple tap). The intensity of the lamp 114 does not change, but any intensity level stored in memory as a locked
25 preset level is cleared.

 If a locked preset level is stored in memory and the control unit 10 is in an off state then a FADE TO PRESET response causes the intensity of the electric lamp 114 to increase to the locked preset level. If no locked preset level is stored in memory and the control unit 10 is in an off state, then a FADE TO
30 PRESET response causes the intensity of the electric lamp 114 to increase to the level at which the lamp 114 was illuminated when the control unit 10 was last in an ON state.

 Although the process of storing and clearing a locked preset level has been described with reference to multiple actuations of the control switch actuator

- 15 -

13, this could also be accomplished by using two additional separate switches, one to store a locked preset level and one to clear the locked preset level, or by using one additional switch, successive actuations of which would alternately store and clear the locked preset power level.

5 If a delay time has been stored by actuating the lower power level selector portion **12b** when the control unit **10** is in the off state as described above, then a FADE TO OFF response effected by a single actuation of transitory duration of the user actuatable control switch actuator **13** when the control unit **10** is in the on state causes the lights to remain at their present intensity for the duration of the
10 stored delay time and then to decrease at a third fade rate to an off state.

FIG. 21 illustrates delay to off profiles for a 20 second delay to off of the control unit **10**. The profiles show how the light intensity levels of the lamp **114** change, starting from their current intensity level for four different beginning intensity levels. The lamp **114** remains at the current intensity level for the delay
15 time in this case 20 seconds before the intensity of the lamp decreases to zero. The delay to off time is variable and the preferred embodiment has a variable delay to off time range of 10 to 60 seconds in 10 second increments. Although these delay times are presently preferred, it should be understood that the delay to off times and the associated fade rate to off at the end of the delay time are not the only ones
20 which may be used with the invention, and any desired delay, fade rate or combination thereof may be employed without departing from the invention.

The control unit **10** will remain at the current intensity level 600 for the duration of the delay time. At the end of the delay time, the intensity of the lamp **114** decreases to zero. A suitable fade rate **602** for the decrease to zero may be 33 %
25 per second. Preferably the delay times and fade rates are stored in the form of digital data in the microprocessor **108**, and may be called up from memory when required by the delay to off routine also stored in memory.

The delay to off profiles illustrated in FIG. 21 for a 20 second delay and similar profiles for the other possible delay to off times are used whether the
30 control unit **10** is performing a DELAY TO OFF in response to an extended actuation of control switch actuator **13** or it is delaying to off with a previously stored delay time in response to transitory actuation of control switch actuator **13**.

- 16 -

The control unit **10** and the cover plate **11** need not be limited to any specific form, and are preferably of a type adapted to be mounted to a conventional wall box commonly used in the installation of lighting control devices.

5 The selection actuator **12** and the control switch actuator **13** are not limited to any specific form, and may be of any suitable design which permits actuation by a user. Preferably, although not necessarily, the actuator **12** controls two separate momentary contact push switches **62a**, **62b**, but may also control a rocker switch, for example, without departing from the invention. Actuation of the upper portion **12a** of the actuator **12** increases or raises the light intensity level, while
10 actuation of lower portion **12b** of the actuator **12** decreases or lowers the light intensity level. Preferably, but not necessarily, the actuator **13** controls a push-button momentary contact type switch **53**, but the switch **53** may be of any other suitable type without departing from the scope of the present invention.

Similarly, although the effect of actuating the control switch actuator
15 **13** is described above with respect to specific actuation sequences of control switch **13** having specific effects, i.e., FADE TO FULL is effected by a double tap and LOCKED PRESET is effected by a triple tap, the linkage between the specific actuation sequence and the specific effect can be changed without departing from the scope of the present invention. For example, in an alternative embodiment of
20 the invention, FADE TO FULL could be effected by a triple tap.

The control unit **10** includes an intensity level indication in the form of a plurality of intensity level indicators **14**. The indicators are preferably, but need not be, light-emitting diodes (LEDs) or the like. Although the intensity level indicators **14** may occasionally be referred to herein for convenience as LEDs, it
25 should be understood that such a reference is for ease of describing the invention and is not intended to limit the invention to any particular type indicator. Intensity level indicators **14** are arranged, in this embodiment, in a linear array representing a range of light intensities of the one or more lamps controlled by the control unit **10**. The range of light intensities is from a minimum (zero, or "off") to a maximum
30 intensity level ("full on"). A visual indication of the light intensity of the controlled lights is displayed by the illumination of a single intensity level indicator **14** preferably at 100% of its output when the lamps are on.

The intensity level indicators **14** of the preferred embodiment illustrated in **FIG. 1** show seven indicators aligned vertically in a linear array. By illuminat-

- 17 -

ing the uppermost indicator in the array, maximum light intensity level is indicated. By illuminating the center indicator, an indication is given that the light intensity level is at about the midpoint of the range, and by illuminating the lowermost indicator in the array, the minimum light intensity level is indicated.

5 Any convenient number of intensity level indicators **14** can be used. By increasing the number of indicators in an array, the finer the gradation between intensity levels within the range can be achieved. In addition, when the lamp or lamps being controlled are off, all of the intensity level indicators **14** can be constantly illuminated at a low level of illumination preferably at 0.5% of their maximum
10 output for convenience of the user. The indicator representing the actual intensity level of the lamps when they return to the on state is illuminated at a slightly higher illumination level, preferably at 2% of its maximum output. These illumination characteristics enable the intensity level indicators **14** to be more readily perceived by the eye in a darkened environment, thereby assisting a user in locating the switch
15 in a dark room, and constitute a "night light mode". An important feature of the present invention, in addition to controlling the lights in the room, is to provide sufficient contrast between the level indicators to enable a user to perceive the actual intensity level at a glance.

The intensity level indicators **14** are also used to provide feedback
20 to the user of the control unit **10** regarding how the control unit **10** is responding to the various actuations of control switch actuator **13** and selection switch actuator **12**.

For example, when a FADE TO PRESET response is effected by a single actuation of transitory duration of control switch actuator **13** when the
25 control unit **10** is in the off state, the intensity level indicators **14** change from the "night light mode" to illuminating the lowermost indicator followed by illuminating successively higher indicators in turn as the light intensity increases until the indicator which indicates the intensity of the preset light level is illuminated.

Further, when a FADE TO FULL response is effected by a double
30 tap of the control switch actuator **13**, the intensity level indicators change from their original condition to illuminating successively higher indicators in turn until the uppermost indicator in the array is illuminated as the light intensity increases to full.

Further, when a FADE TO OFF response is effected by a single actuation of transitory duration of the control switch actuator **13** when the control

- 18 -

unit **10** is in the on state, the intensity level indicators **14** change from their original condition to illuminating successively lower indicators in turn as the light intensity decreases to its lowest level. Finally, the intensity level indicators **14** indicate the "night light mode" when the light intensity decreases to zero.

5 Further, when a DELAY TO OFF response is effected by extended actuation of the control switch actuator **13** when the control unit **10** is in the on state, the intensity level indicators **14** first indicate the length of the delay time selected. After the control switch actuator **13** has been held closed for 0.5 seconds, the lowermost indicator will cycle on and off to indicate that a 10 second delay has been
10 selected, after a further 0.5 seconds the next highest indicator will cycle on and off to indicate that a 20 second delay has been selected, and so on, with successively higher indicators cycling on and off until the control switch actuator **13** is released.

 When the control switch actuator **13** is released, the indicator indicating the present light intensity level cycles on and off during the delay time.
15 At the end of the delay time, the indicator which indicates the present level is illuminated and then successively lower indicators are illuminated as the light decreases to its lowest level. Finally, the intensity level indicators **14** indicate the "night light mode" when the light intensity decreases to zero.

 When a LOCKED PRESET response is effected by a triple actuation
20 of the control switch actuator **13**, the intensity level indicator indicating

the current light level of the lamp flashes twice at a frequency of 2Hz to indicate that the intensity level has been successfully stored.

 When a DISCONTINUE LOCKED PRESET response is effected by a quadruple actuation of the control switch actuator **13**, the intensity level
25 indicator indicating the current light level of the lamp flashes twice at a frequency of 2Hz to indicate that the intensity level has been cleared from memory.

 When a RAISE response is effected by actuation of the upper portion
30 **12a** of the selection actuator **12**, the intensity level indicators **14** change from their original condition to illuminating successively higher indicators in turn as the actuation continues until either the actuation ends or the uppermost indicator in the array is illuminated when the light intensity reaches a maximum.

 When a LOWER response is effected by actuation of the lower portion **12b** of selection actuator **12** while the control unit **10** is in the on state, the

- 19 -

intensity level indicators **14** change from their original condition to illuminating successively lower indicators as the actuation continues until either the actuation ends or the lowermost indicator in the array is illuminated when the light intensity reaches a minimum. The control unit **10** does not turn off.

5 Finally, if the lower portion **12b** of the selection actuator **12** is actuated when the control unit **10** is in the off state, the intensity level indicators **14** initially indicate the "night light mode". After the lower portion **12b** has been actuated for 4.0 seconds, the lowermost indicator will cycle on and off to indicate that a 10 second delay has been selected, after a further 0.5 seconds the next highest
10 indicator will cycle on and off to indicate that a 20 second delay has been selected, and so on, with successively higher indicators cycling on and off until the lower portion **12b** is released. When the lower portion **12b** is released, the indicator indicating the delay time selected flashes twice at a frequency of 2Hz to indicate that the delay time has been successfully stored and then the intensity level indicators
15 **14** return to the "night light mode".

WIRELESS TRANSMITTER UNITS

One embodiment of a basic infrared signal transmitting wireless remote control unit **20** suitable for use with the control unit **10** is shown in **FIGS. 2, 2A, 2B and 2C.**

20 The basic wireless control unit **20** comprises a plurality of control actuators, comprising a user actuatable transmitter power level selection actuator **23** and associated intensity selection switches **223** and a user actuatable transmitter control switch actuator **21** and associated transmitter control switch **221**. Transmitter selection actuator **23** further comprises an increase power level selector portion **23a**
25 and a decrease power level selector portion **23b**, controlling respective intensity selection switches **223a, 223b.**

 The basic wireless control unit **20** further comprises an infra-red transmitting diode **26** which is located in an opening **25** in an end **24** of the basic wireless control unit **20** as best seen in **FIG. 2C.** Alternatively, basic wireless
30 control unit **20** can further comprise an address switch **222** and an address switch actuator **22**, which may be used in conjunction with a "send address" switch (not shown) as will be described in more detail below. The switches **221, 222, 223a, 223b** are shown in **FIG. 11.**

- 20 -

Actuation of the increase power level selector portion **23a**, the lower power level selector portion **23b**, or the transmitter control switch actuator **21** of basic wireless remote control unit **20** generally has the same effect as actuating the upper power level selector portion **12a**, the lower power level selector portion **12b** or the control switch actuator **13** respectively of the control unit **10**.

The actuation of the actuators **23a**, **23b**, **21** on the basic wireless remote control unit **20** closes the respective switches **223a**, **223b**, **221** which they actuate. The switch closure is detected by a microprocessor **27** and the information about which actuator has been operated is transmitted via infra-red signals from the infra-red transmitting diode **26** as will be described in more detail below in connection with the description of **FIGS. 6 and 11**.

The infrared signals are detected by an infra-red receiver **104** and the signal information is passed to a microprocessor **108** which interprets the signal information as will be described in more detail below in connection with the description of **FIGS. 10 and 13 to 20**.

In general, actuating an actuator on the basic wireless remote control unit **20** has the same effect as operating the corresponding actuator on the control unit **10**. Thus, actuating the transmitter control switch actuator **21** for a transitory period of time will have the same effect as operating the control switch actuator **13** on the control unit **10** for a transitory period of time. (As described above, the exact effect may vary depending on the state of the control unit **10** prior to the actuation). However, if desired, certain functions may be accessed only from the control unit **10** and not from basic wireless remote control unit **20** or vice versa. For example, the triple tap of transmitter control switch actuator **21** could have no effect on the control unit **10**, whereas the triple tap of control switch actuator **13** could have the effect described above.

One embodiment of an enhanced infra-red signal transmitting wireless remote control unit **30** suitable for use with the control unit **10** is shown in **FIGS. 3, 3A and 3B**. The enhanced wireless control unit **30** comprises a plurality of control actuators, comprising a user actuatable transmitter power level selection actuator **33** and associated intensity selection switches **333**, and a user actuatable transmitter scene control actuator **31** and associated switches **331**. Transmitter selection actuator **33** further comprises an increase power level selector portion **33a** and a decrease power level selector portion **33b**, controlling respective intensity

- 21 -

selection switches **333a** and **333b**, and scene the control actuator **31** further comprises a scene select actuator **31a** and an off actuator **31b** controlling respective scene control switches **331a**, **331b**.

5 The enhanced wireless control unit **30** further comprises an infra-red transmitting diode **36** which is located in an opening **35** in an end **34** of the enhanced wireless control unit **30** as best seen in **FIG. 2B**. Alternatively the enhanced wireless control unit **30** can further comprise an address switch **332** and address switch actuator (not shown but the same as the address switch actuator **22** used with the basic wireless control unit **20**). The switches **331a**, **331b**, **332**, **333a**, **333b** are
10 shown in **FIG. 12A**.

Actuation of the increase power level selector portion **33a** or the lower power level selector portion **33b** of the enhanced wireless control unit **30** generally has the same effect as actuating the upper power level selector portion **12a** or the lower power level selector portion **12b** of the control unit **10**, respectively.

15 Actuation of the scene select actuator **31a** for a transitory period of time causes the light intensity of the electric lamp **114** to change at the first fade rate from its present intensity level (which can be off) to a first preprogrammed preset intensity level.

Actuation of the scene select actuator **31a** for two transitory periods
20 of time in rapid succession causes the light intensity of the electric lamp **114** to change at the first fade rate from its present intensity level (which can be off) to a second preprogrammed preset intensity level.

The method for preprogramming the preset intensity levels will be described in detail below.

25 Actuation of the off actuator **31b** generally has the same effect as actuating the control switch actuator **13** of the control unit **10** when the control unit **10** is in an on state and is delivering a non-zero power level to the lamp under control; and has no effect when the control unit **10** is in an off state and delivering zero power to the lamp. Hence, by actuating the off actuator **31b**, it is possible to
30 effect a fade to off response or a delay to off response from the control unit **10**.

The actuation of the actuators **33a**, **33b**, **31a**, **31b** which they actuate on the enhanced wireless remote control unit **30** closes the respective switches **333a**, **333b**, **331a**, **331b**. The switch closure is detected by a microprocessor **47**, and the information about which actuator has been operated is transmitted via infra-red

- 22 -

signals from the infra-red transmitting diode **36** as will be described in more detail below in connection with the description of **FIGS. 6 AND 12A**.

5 The infrared signals are detected by an infra-red receiver **104** and the signal information is passed to a microprocessor **108** which interprets the signal information as will be described in more detail below in connection with the description of **FIGS. 10 AND 13-20**.

10 A second embodiment of an enhanced infra-red transmitting wireless remote control unit **40** suitable for use with the control unit **10** is shown in **FIGS. 4 AND 4A**. The enhanced wireless control unit **40** comprises a plurality of control actuators, comprising a user actuatable transmitter power level selection actuator **43** and associated intensity selection switches **443**, and user actuatable transmitter scene control actuators **41** and associated switches **441**. The transmitter selection actuator **43** is a paddle actuator which is moved upwards to actuate increase intensity selection switch **443a** and is moved downwards to actuate decrease intensity selection switch **443b**. The scene control actuators **41** comprise scene select actuators **41a**, **41b**, **41c**, **41d** and an off actuator **41e** controlling respective scene control switches **441a**, **441b**, **441c**, **441d**, **441e**.

15 The enhanced wireless control unit **40** further comprises an infra-red transmitting diode **46** which is located in an opening **45** in an end **44** of the enhanced wireless control unit **40** as best seen in **FIG. 4A**. Alternatively enhanced wireless control unit **40** can further comprise an address switch **442** and an address switch actuator (not shown but the same as the address switch actuator **22** used with the basic wireless control unit **20**). The switches **441a**, **441b**, **441c**, **441d**, **441e**, **442**, **443a**, **443b** are shown in **FIG. 12B**.

25 Actuation of increase intensity switch **443a** by moving the transmitter selection actuator upward generally has the same effect as actuating the upper power level selector portion **12a** of the control unit **10**. Similarly, actuation of decrease intensity selection switch **443b** by moving the transmitter selection actuator downward generally has the same effect as actuating the lower power level selector portion **12b** of the control unit **10**.

30 Actuation of each of the scene select actuators **41a**, **41b**, **41c**, **41d** for a transitory period of time causes the light intensity of the electric lamp **114** to change at the first fade rate from its present intensity level (which can be off) to first, second, third, and fourth preprogrammed preset intensity levels, respectively.

- 23 -

Actuation of each of the scene select actuators **41a, 41b, 41c, 41d** for two transitory periods of time in rapid succession causes the light intensity of the electric lamp **114** to change at the first fade rate from its present intensity level (which can be off) to fifth, sixth, seventh, and eighth preprogrammed preset intensity levels, respectively.

The method for preprogramming the preset intensity levels will be described in detail below.

Actuation of the off actuator **41e** generally has the same effect as actuating the control switch actuator **13** of the control unit **10** when the control unit **10** is in an on state and is delivering a non-zero power level to the lamp under control; and has no effect when control unit **10** is in an off state and delivering zero power to the lamp. Hence, by actuating the off actuator **41e**, it is possible to effect a fade to off response or a delay to off response from the control unit **10**.

The actuation of the actuators **43, 41a, 41b, 41c, 41d, 41e** on the enhanced wireless remote control unit **30** closes the respective switches **443a, 443b, 441a, 441b, 441c, 441d, 441e** which they actuate. The switch closure is detected by a microprocessor **47**, and the information about which actuator has been operated is transmitted via infra-red signals from the infra-red transmitting diode **46** as will be described in more detail below in connection with the description of **FIGS. 6 AND 12B**.

The infra-red signals are detected by an infra-red receiver **104** and the signal information is passed to a microprocessor **108** which interprets the signal information as will be described in more detail below in connection with the description of **FIGS. 10 AND 13-20**.

A third embodiment of an enhanced infra-red transmitting wireless remote control unit **50** suitable for use with the control unit **10** is shown in **FIGS. 5 AND 5A**.

The enhanced wireless control unit **50** comprises a plurality of control actuators comprising a user actuatable transmitter power level selection actuator **53** and associated intensity selection switches **553**, and user actuatable transmitter scene control actuators **51** and associated switches **551**. The transmitter selection actuator **53** is a paddle actuator which is moved upwards to actuate increase intensity selection switch **553a** and is moved downwards to actuate decrease intensity selection switch **553b**. The scene control actuators **51** comprise scene select actuators **51a, 51b, 51c**,

- 24 -

51d and an off actuator **51e** controlling respective scene control switches **551a**, **551b**, **551c**, **551d**, **551e**. The scene control actuator **51** further comprise special function select actuators **51f**, **51g**, **51h**, **51i** controlling respective special function control switches **551f**, **551g**, **551h**, **551i**.

5 The enhanced wireless control unit **50** further comprises an infra-red transmitting diode **56** which is located in an opening **55** in an end **54** of the enhanced wireless control unit **50** as best seen in **FIG. 5A**. Alternatively enhanced wireless control unit **50** can further comprise an address switch **552** and an address switch actuator (not shown but the same as the address switch actuator **22** used with the
10 basic wireless control unit **20**). The switches **551a**, **551b**, **551c**, **551d**, **551e**, **551f**, **551g**, **551h**, **551i**, **552**, **553a**, **553b** are shown in **FIG. 12C**.

 Actuation of increase intensity switch **553a** by moving the transmitter selection actuator upward generally has the same effect as actuating the upper power level selector portion **12a** of the control unit **10**. Similarly, actuation of decrease
15 intensity selection switch **553b** by moving the transmitter selection actuator downward generally has the same effect as actuating the lower power level selector portion **12b** of the control unit **10**.

 Actuation of each of the scene select actuators **51a**, **51b**, **51c**, **51d** for a transitory period of time causes the light intensity of the electric lamp **114** to
20 change at the first fade rate from its present intensity level (which can be off) to first, second, third, and, fourth preprogrammed preset intensity levels, respectively.

 Actuation of each of the scene select actuators **51a**, **51b**, **51c**, **51d** for two transitory periods of time in rapid succession causes the light intensity of the electric lamp **114** to change at the first fade rate from its present intensity level
25 (which can be off) to fifth, sixth, seventh, and eighth preprogrammed preset intensity levels, respectively.

 The third embodiment **50** of the enhanced transmitter differs from the second embodiment **40** of the enhanced transmitter in that it further comprises special function actuators **51f**, **51g**, **51h**, **51i** controlling respective special function
30 switches **551f**, **551g**, **551h**, **551i**. These special function actuators can be used to select ninth, tenth, eleventh, and twelfth preprogrammed preset intensity levels, respectively, or to select special functions. Alternatively, some special function actuators can be used to select preprogrammed preset intensity levels and some can be used to select special functions.

- 25 -

The method for preprogramming the preset intensity levels and the nature of the special functions will be described in detail below.

Actuation of the off actuator **51e** generally has the same effect as actuating the control switch actuator **13** of the control unit **10** when the control unit
5 **10** is in an on state and is delivering a non-zero- power level to the lamp under control; and has no effect when control unit **10** is in an off state and delivering zero power to the lamp. Hence, by actuating the off actuator **51e**, it is possible to effect a fade to off response or a delay to off response from the control unit **10**.

The actuation of the actuators **53, 51a, 51b, 51c, 51d, 51e, 51f, 51g, 51h, 51i** on the enhanced wireless remote control unit **30** closes the respective
10 switches **553a, 553b, 551a, 551b, 551c, 551d, 551e, 551f, 551g, 551h, 551i** which they actuate. The switch closure is detected by a microprocessor **47**, and the information about which actuator has been operated is transmitted via infra-red signals from the infra-red transmitting diode **56** as will be described in more detail
15 below in connection with the description of **FIGS. 6 AND 12C**.

The infra-red signals are detected by an infra-red receiver **104** and the signal information is passed to a microprocessor **108** which interprets the signal information as will be described in more detail below in connection with the description of **FIGS. 10 AND 13-20**.

20 The method for preprogramming the preset intensity levels accessed from the enhanced wireless control units **30, 40, 50** is similar for each of the enhanced remote controls.

Programming mode for the control unit **10** is entered by actuating a combination of actuators on the enhanced remote controls and keeping the switches
25 controlled by the actuators closed for a certain length of time, preferably 3 seconds, while transmitting infra-red signals from the transmitter to control unit **10** at which time the control unit **10** enters programming mode.

For the embodiment of the enhanced remote control **30** illustrated in **FIGS. 3, 3A AND 3B**, programming mode is entered by actuating the scene select
30 actuator **31a** and the off actuator **31b** at the same time. For the embodiment **40** illustrated in **FIGS. 4 AND 4A**, programming mode is entered by actuating the scene select actuator **41a** and the off actuator **41e** at the same time. For the embodiment **50** illustrated in **FIGS. 5 AND 5A**, programming mode is entered by actuating the scene select actuator **51a** and the off actuator **51e** at the same time.

- 26 -

The control unit **10** enters the programming mode ready to program the first preset intensity level. The uppermost indicator **14** (which is indicating that the first preset intensity level is being programmed) flashes on and off with a duty cycle of approximately 10% and the indicator **14** corresponding to the light intensity level currently programmed as the first preset intensity level flashes on and off with a 90% duty cycle. Duty cycle here refers to the relative amount of time that one indicator **14** is on as opposed to another indicator **14** being on. Only one indicator **14** is ever illuminated at one time due to constraints within the power supply powering the indicator **14**.

The light intensity level to be stored is adjusted by actuating the increase power level selector portion **33a** or lower power level selector portion **33b** or the off actuator **31b** for the embodiment of the enhanced remote control **30** illustrated in **FIGS. 3, 3A AND 3B**, by actuating the power level selection actuator **43** either up or down to actuate increase intensity selection switch **443a** or decrease intensity selection switch **443b** or the off actuator **41e** for the embodiment of the enhanced remote **40** illustrated in **FIGS. 4 AND 4A**, by actuating the power level selection actuator **53** either up or down to actuate increase intensity selection switch **553a** or decrease intensity selection switch **553b** or the off actuator **51e** for the embodiment of the enhanced remote **50** illustrated in **FIGS. 5 AND 5A**. For all embodiments of the enhanced remote control **30, 40, 50**, the light intensity to be stored can also be adjusted by actuating the upper power level selection portion **12a** and the lower power level selector portion **12b** of the control unit **10**.

As the intensity is adjusted, the light intensity of electric lamp **114** changes and the indicator **14** which is illuminated with a 90% duty cycle also changes to indicate the new current light level.

Once the desired intensity level to be programmed as the first preset intensity level (which may be off), has been reached either another preset intensity level to be programmed is selected or programming mode is exited. In the case of the enhanced remote control **30** illustrated in **FIGS. 3, 3A AND 3B**, only a first preset intensity level can be programmed, so the only option at this point is to exit programming mode.

If it is desired to program another preset intensity level, then this is selected by actuating a scene select actuator **41b, 41c, 41d** for a transitory period of time for the embodiment of the enhanced remote control illustrated in **FIGS. 4**

- 27 -

AND 4A or a scene select actuator 51b, 51c, 51d for a transitory period of time for the embodiment of the enhanced remote control illustrated in FIGS. 5 AND 5A.

These scene select actuators select second, third, and fourth preset intensity levels to be programmed respectively. The second highest indicator 14
5 flashes on and off with a 10% duty cycle when the second preset intensity level has been selected, the third highest indicator 14 flashes on and off with a 10% duty cycle when the third preset intensity level has been selected and the middle indicator 14 flashes on and off with a 10% duty cycle when the fourth preset intensity level has been selected.

10 Actuating a scene select actuator 41a, 41b, 41c, 41d, 51a, 51b, 51c, 51d for two transitory periods of time enables the selection of the fifth, sixth, seventh, and eighth preset intensity levels to be programmed, respectively.

The highest, second highest, third highest, and middle indicator 14 will flash on and off with a duty cycle other than 10% to indicate that either the fifth,
15 sixth, seventh, or eighth preset intensity level to be programmed has been selected.

If the embodiment of the enhanced transmitter 50 illustrated in FIGS. 5 AND 5A is being used to select ninth, tenth, eleventh, and twelfth preset intensity levels from the special function actuators 51f, 51g, 51h, 51i, these can be selected for programming by actuating a special function actuator 51f, 51g, 51h, 51i.

20 The highest, second highest, third highest, and middle indicator 14 will flash on and off with a second duty cycle other than 10% to indicate that either the ninth, tenth, eleventh, or twelfth preset intensity level to be programmed has been selected.

25 The light intensity to be stored is adjusted in the same manner as described above for programming the first preset intensity level.

Once all the desired preset intensity levels have been programmed, programming mode is exited by actuating the same combination of actuators which were used to enter programming mode again for a period of time, preferably 3 seconds, while transmitting infra-red signals from the transmitter to the control unit
30 10. At the end of the period, the control unit exits programming mode. Alternatively, programming mode can be exited by actuating actuator 13 on control unit 10 for a transitory period of time.

- 28 -

The operation of the special function actuators **51f, 51g, 51h, 51i** on the enhanced transmitter **50** is dependant on the particular special functions programmed into the control unit **10** which receives the infrared signals.

One alternative is to use the special function selection actuator to
5 select additional programmed intensity levels as described above. A first special function which can be selected by a first special function actuator is "FADE TO OFF WITH DETERMINED FADE TIME". This function is similar to "DELAY TO OFF" except that, whereas in the case of the "DELAY TO OFF" the light intensity of lamp **114** remains at its current intensity during the delay time and then decreases
10 to zero over a relatively short period of time, in the case of "FADE TO OFF WITH DETERMINED FADE TIME" the light intensity level of lamp **114** immediately begins to decrease in value once the actuator is released and then continues to decrease in value until it reaches zero at the end of the "DETERMINED FADE TIME".

15 The "DETERMINED FADE TIME" is determined by the length of time that the first special function actuator has been actuated. The longer the actuator is actuated, the longer the fade time.

After the first special function actuator has been actuated the indicator **14** will flash the lowest LED to indicate a fade time of 10 sec has been selected.
20 For each additional 0.5 sec that the first special function actuator is actuated the fade time increases by 10 sec to a maximum of 60 sec. Successively higher indicators **14** are flashed to indicate the increasing fade time selected. When the first special function actuator is released, the decrease in light intensity of lamp **114** begins to occur and the indicator **14** indicating the current light intensity is flashed.
25 Successively lower indicators **14** are flashed as the light intensity of lamp **14** is decreased until the indicator **14** indicates the "Night light mode" when lamp **114** is at zero power.

A second special function which can be selected by a second special function actuator is "RETURN TO PREVIOUS LIGHT LEVEL". This function
30 causes the light intensity of lamp **114** to return to the last preset level it had prior to the last actuation of a scene select actuator, a control switch actuator, or a power level selector actuator.

In this way it is possible for the user of the control unit **10** to return to the last selected preset level which could be a preprogrammed preset intensity

- 29 -

level, a locked preset intensity level or an unlocked preset intensity level. The intensity level of lamp **114** will gradually increase or decrease from the current intensity level to the intensity level being returned to, and the indicator **14** will change from illuminating the LED corresponding to the current intensity level to
5 illuminating successively higher or lower LEDs until the indicator **14** indicating the intensity level of the last selected preset level is illuminated.

Other special functions can optionally be programmed into the control unit **10** and selected by actuating different special function actuators.

The operation of the optional address switch actuator **22** and address
10 switch **222, 332, 442, 552** and the send address switch (not shown) is similar for the basic wireless control unit **20**, and the three embodiments of the enhanced wireless control unit **30, 40, 50**.

The first use of the optional address switch actuator **22** and the send address switch is to label control unit **10** with a particular address. Address switch
15 actuator **22** controls an address switch, **222, 332, 442, 552** which is typically a multiposition switch, for selecting between different address **A, B, C, D**, etc. If it is desired to label a particular control unit **10** with address **B**, then the address switch actuator would be adjusted to select **B**, and then the send address switch would be actuated. The send address switch is not shown, but could have any
20 desired form. Preferably, the send address switch is actuated by a small and inconspicuous actuator since it is used infrequently. Alternatively, the actuator for the send address switch could be hidden under normal use for, for example under a battery compartment cover for the wireless control unit **20, 30, 40, 50**.

Alternatively in the case of the three embodiments of enhanced
25 wireless control unit **30, 40, 50**, the function of the send address switch could be obtained by actuating a combination of the existing actuators, for example the off actuator **31b, 41e, 51e** and the upper power level selector portion **33a**, or moving the transmitter selection actuator **43, 53** upwards.

After the send address switch has been actuated or the appropriate
30 combination of actuators has been actuated, an infrared signal is sent from the wireless control unit **20, 30, 40, 50** which commands any control unit **10** which receives the signal to label itself with address **B**. The intensity level indicator **14** indicating the current intensity level of the lamp flashes three times at a frequency

- 30 -

of 2Hz to indicate that the address has been successfully received and stored in a memory.

Alternatively, the intensity level indicator **14** indicating the current intensity level of the lamp **114** flashes at a frequency of 2Hz until the control switch actuator **13** is actuated for a transitory period of time to store the address in memory. If actuator **13** has not been actuated within 2 minutes of the control unit **10** receiving the infra-red signal, then no address is stored and the control unit **10** returns to the state which it was in prior to receiving the infra-red signal.

In this way, it is possible to label a plurality of control units **10** with the same or different addresses.

Once all the control units **10** desired to be controlled by the wireless control unit **20**, **30**, **40**, **50** have been labelled with addresses, then the wireless control unit **20**, **30**, **40**, **50** can be used to control only those control units **10** which have been labelled with a particular address in the following manner.

The address switch actuator **22** is adjusted to the position which selects the address of the control units **10** which were desired to be controlled, for example **A**. After that has been done, any signals sent from wireless control unit **20**, **30**, **40**, **50** in response to the actuation of the other actuators, for example scene select actuation **31**, **41**, **51** or transmitter selection actuator **33**, **43**, **53** contain address information **A**.

Only those control units **10** which have previously been labelled with address **A** will respond to the infra-red signals which contain address information **A**. Other control units **10** will not respond. In this way, by labelling a plurality of control units **10** with different addresses, it is possible to control each control unit **10** individually, even if all units receive the infra-red signals.

It is also possible for the address switch actuator **22** to select an **ALL** address. This cannot be used to label control units **10**. However, once the control units **10** have been labelled with individual addresses **A**, **B**, **C**, etc., then selecting the **ALL** address with the address switch actuator **22** causes the infra-red signals transmitted from wireless control unit **20**, **30**, **40**, **50** to contain an **ALL** address. In this case, all control units **10** which receive the infra-red signals with the **ALL** address will respond regardless of the individual addresses with which they have been labelled.

- 31 -

Turning to **FIG. 10**, the circuitry of the power control unit 10 is depicted in the control unit block diagram **100**. The circuitry, with the exception of wireless remote control operation, is well known to one skilled in the art, and is fully described in U.S. Patent 5,248,919 which has been incorporated herein by reference. Therefore, a detailed description of the prior art circuit is not reproduced herein, and only the new features of the present invention are described below.

The preferred embodiment of the present invention provides the features of wireless remote control operation, as described below, in combination with the light control disclosed in U.S. Patent 5,248,919. In the preferred embodiment of the present invention, the circuitry of the power control unit 10 is commanded by infra-red control signals transmitted by wireless remote control units **20, 30, 40, 50**, (shown in **FIGs. 2, 3, 4 and 5**, respectively) in addition to being commanded by actuators located on the power control unit 10. An infrared receiver **104** responds to the infra-red control signals and converts them to electrical control signal inputs to a microprocessor **108** in a similar manner to which the signal detector **102** responds to control signals from switches **110** located in power control unit 10 as well as control signals from switches **111** within wired remote lighting control units and provides control signal inputs to microprocessor **108** of the present invention are similar to the control signals, signal detector **32**, and microprocessor **28** disclosed in U.S. Patent 5,248,919. However, the program running is different and provides additional functions and features not disclosed in U.S. Patent 5,248,919.

In the present invention, control signal inputs are generated by switch actuators on the power control unit 10, by switch actuators on a user actuatable wireless remote control unit **20, 30, 40, 50**, or on wired remote lighting control units. In each case, these signals are directed to the microprocessor **108** for processing. The microprocessor **108** then sends the appropriate signals on to the remaining portion of the control circuitry which in turn control the intensity levels and state of the lamp **114** associated with the control unit 10.

A block diagram of the control circuit **200** of basic remote control unit **20** is depicted in **FIG. 11**. The intensity selection actuator **23** actuates intensity selection switches **223a** or **223b** and the control switch actuator **21** actuates transmitter control switch **221** to provide inputs to a microprocessor **27**. The microprocessor **27** provides encoded control signals to an LED drive circuit **28**,

- 32 -

which drives an LED 26 to produce and transmit infrared signals encoded by the microprocessor 27. The LED 26 is located in the IR transmitter opening 25, embodied in the end wall 24 of the user actuatable basic remote control unit 20.

5 The address switch actuator 22 actuates the address switch 222 to provide inputs to the microprocessor 27. A "SEND ADDRESS" switch not shown in FIG. 11 would also provide input to the microprocessor 27 as described above.

Battery 49 provides power to basic remote control unit 20.

10 The microprocessor 27 has a preprogrammed software routine which controls its operation. The operation of the routines in the microprocessor 27 is illustrated in flow chart form in FIG. 6. There is one major flow path, or routine, which the program in the microprocessor 27 follows. This path is selected whenever the "ACTUATOR OR ACTUATORS OPERATED?" decision node 2000 is "yes". This occurs whenever the control switch actuator 21 or the power level selection actuator 23 is actuated. Following the "ACTUATOR OR ACTUATORS
15 OPERATED?" decision node is the "DETERMINE WHICH ACTUATOR OR ACTUATORS WERE OPERATED?" node 2004 where a determination is made as to which actuator or actuators were operated. Following the "DETERMINE WHICH ACTUATOR OR ACTUATORS WERE OPERATED" node 2004 is the "DETERMINE ADDRESS" node 2006, where the microprocessor 27 determines
20 the setting of the address switch 222. The microprocessor 27 then proceeds to "LOOK UP A NUMBER WHICH CORRESPONDS TO THE ACTUATOR OR ACTUATORS OPERATED AND THE ADDRESS SELECTED" 2008. The microprocessor then "ENCODES NUMBER" 2010 and then "TRANSMITS CODE" 2012.

25 If the control switch actuator 21 or power level selection actuator 23 is not actuated by a user, the remote control unit 20 enters a "SLEEP MODE" 2002 and no change is made to the state of the control unit 10.

30 A block diagram of each of the control circuits 300, 400, 500 of the enhanced wireless remote control units 30, 40, 50 is depicted in FIGs. 12A, 12B, 12C. These block diagrams are very similar to the block diagram 200 shown in FIG. 11 with the scene control switches 331a, 331b in the block diagram 300 replacing the transmitter control switch 221 in the block diagram 200, the scene control switches 441a, 441b, 441c, 441d, 441e in the block diagram 400 replacing the transmitter control switch 221 in the block diagram 200, and the scene control

- 33 -

switches **551a, 551b, 551c, 551d, 551e**, and special function switches **551f, 551g, 551h, 551i** in the block diagram **500** replacing the transmitter control switch **221** in the block diagram **200**.

The scene control switches provide inputs to the microprocessor **47**.

5 The microprocessor **47** provides encoded control signals to an LED drive circuit **48** which drives an LED **36, 46, 56** to produce and transmit infrared signals encoded by the microprocessor **47**. These signals are transmitted through the IR opening **35, 45, 55** which is located in the end wall **34, 44, 54** of the enhanced wireless remote control units **30, 40, 50**.

10 An address switch actuator **22** of the enhanced remote control units **30, 40, 50** actuates the address switch **332, 442, 552** respectively to provide inputs to the microprocessor **47**. A send address switch, not shown in **Figures 12A, 12B, and 12C** would also provide input to the microprocessor **47**.

15 The enhanced remote control units **30, 40, 50** use the same preprogrammed software routine to control their operation as depicted in **FIG. 6**. The actual code running may be different. The "ACTUATOR OR ACTUATORS OPERATED" decision node **2000** in **FIG. 6** is "yes" whenever a scene control switch or a power level intensity selector switch is actuated.

Turning to **FIGs 13 through 20**, the microprocessor **108** of the control unit **10** has preprogrammed software routines which control its operation. The operation of the routines in the microprocessor **108** is illustrated in flow chart form in **FIG 13 through 20**. Referring to **FIG 13**, there are four major flow paths, or routines, which the microprocessor **108** can follow. These paths are selected depending on the source of the input control signals. The first three paths, **RAISE 1030, LOWER 1024, and TOGGLE 1036** are selected when the power selection actuator **12** or the control switch actuator **13** are actuated, as discussed above.

The function of the preprogrammed software routines for the operation by wireless remote control will also be discussed in detail, this is the fourth path, "IR SIGNAL" **1012**.

30 Referring to **FIG 13**, the program begins at "MAIN" **1000** as shown. The first decision node encountered is the "IN IR PROGRAM MODE?" **1002**. The program determines if the control unit **10** is in program mode so that preprogrammed light intensities can be stored. If the output from "IN IR PROGRAM MODE" decision node **1002** is "yes", the next decision node is "HAS

- 34 -

AN ACTUATOR OR IR SIGNAL BEEN RECEIVED WITHIN THE LAST TWO MINUTES?" 1004. Decision node 1004 performs a time out function to determine if the user is confused while in programming mode. If the user does not touch the actuators on the control unit within two minutes, the unit will automatically exit from program mode and stop flashing indicators 14 that are being flashed. If the output from decision node 1004 is "no", the control unit 10 is commanded to "EXIT PROGRAM MODE" 1026 and "STOP FLASHING LEDS" 1028 and the program returns to "MAIN" 1000. If the output from decision node 1004 is "yes", the program proceeds to the "ACTUATOR OPERATED?" decision node 1006. A check is made as to whether any actuators have been actuated on the control unit 10 i.e., the power level selection actuator 12 or the control switch actuator 13.

If the output of the "ACTUATOR OPERATED?" decision node 1006 is "yes", the program proceeds to "IN IR PROGRAM MODE?" decision node 1018, where a check is made as to whether the control unit 10 is in program mode again. If the output of the "IN IR PROGRAM MODE?" decision node 1018 is "yes", the program proceeds to "GO TO IR PROGRAM MODE ROUTINE" 1020. This is shown in greater detail in the IR Program Mode routine 1100, shown in FIG 14.

If the output from decision node 1018 is "no", the program proceeds to the "RAISE?" decision node 1030 where a check is made as to whether the upper power level selector portion 12a has been actuated. If the output from the "RAISE" decision node is "yes", the program proceeds to the "GO TO RAISE ROUTINE" 1032. The "RAISE" routine 1400 is shown in greater detail in FIG 16.

If the output of the "RAISE" decision node 1030 is "no", the program proceeds to the "LOWER?" decision node 1022 where a check is made as to whether the lower power level selector portion 12b has been actuated. If the output from the "LOWER" decision node 1022 is "yes", the program proceeds to the "GO TO LOWER ROUTINE" 1024. The "LOWER" routine 1200 is shown in greater detail in FIG 15.

If the output from the "LOWER?" decision node 1022 is "no", the program proceeds to the "TOGGLE?" decision node 1034 where a check is made as to whether the control switch actuator 13 has been actuated. If the output of the "TOGGLE" decision node 1034 is "yes", the program proceeds to the "GO TO TOGGLE ROUTINE" 1036. The "TOGGLE" routine 1300 is shown in greater

- 35 -

detail in FIG 17. If the output of the "TOGGLE" node 1034 is "no", the program then returns to "MAIN" 1000.

If the output of the "ACTUATOR OPERATED?" decision node 1006 is "no", the program proceeds to the "HAS AN ACTUATOR BEEN OPERATED
5 IN THE LAST TWO MINUTES?" decision node 1008. The decision node 1008 runs another time out check to determine if any control actuators have been operated in the last two minutes. If the output from the decision node 1008 is "yes", the program proceeds to the "IR SIGNAL?" decision node 1010 where a determination is made as to whether an IR signal has been received. If the output of the "IR
10 SIGNAL?" decision node 1010 is "yes", the program proceeds to "GO TO IR SIGNAL ROUTINE" 1012. The "IR SIGNAL ROUTINE" 1500 is shown in greater detail in FIGs 18, 19, 20. If the output of the "IR SIGNAL?" decision node 1010 is "no", the program proceeds to "UPDATE LEDS" 1014 where the status of the intensity indicators 14 are updated, and the program returns to "MAIN" 1000. The
15 control unit 10 is constantly updating the LED display even if no actuators are actuated or if no IR signals are received. If the "HAS AN ACTUATOR BEEN OPERATED IN THE LAST TWO MINUTES?" decision node 1008 is "no", the program proceeds to "RESET LEARN ADDRESS MODE" 1016 and then proceeds on to the "IR SIGNAL?" decision node 1010.

20 After the program proceeds to the "LEARN ADDRESS MODE?" 1590, which will be described in more detail below, and "SAVE NEW ADDRESS" 1580, the program is looking for a confirmation signal. If the control unit does not receive the confirmation signal within two minutes the "LEARN ADDRESS MODE" is reset and the new address received is erased.

25 Turning now to FIG 14, the first decision node encountered in "IR PROGRAM MODE" is "TOGGLE?" 1102. IR program mode is where preset light intensity levels can be stored in the control unit 10 by actuating actuators on the control unit 10 or on an enhanced wireless transmitter 30, 40, 50. At the
30 "TOGGLE" decision mode 1102 a determination is made as to whether the control switch actuator 13 has been actuated. If the output of the node is "yes", the control unit 10 is commanded to "STOP FLASHING LEDS" 1104 where any flashing indicators 14 are extinguished. The program continues to "EXIT PROGRAM MODE" 1106, and "UPDATE LEDS" 1108 where the indicators 14 are updated to the correct status, and the program proceeds to "RETURN TO TOP OF MAIN"

- 36 -

1110. This is one way of exiting program mode. Another way will be described in detail below.

If the output of "TOGGLE?" decision node 1102 is "no", the next decision node is "RAISE?" 1112 where a determination is made as to whether the upper power level selector portion 12a has been actuated. If the output of the node is "yes", the program moves on to the "AT HIGH END?" decision node 1114. If the output of the "AT HIGH END?" decision node 1114 is "yes", the light intensity of the lamp 114 can not be increased any more, so no changes are made and the program proceeds "RETURN TO TOP OF MAIN" 1110. If the output of the "AT HIGH END?" decision node 1114 is "no", the control unit 10, is commanded to "INCREASE LIGHT LEVEL BY ONE STEP" 1116 where the output power of the control unit 10 is increased. The program continues to "DETERMINE SCENE" 1118 where the program checks which scene is being programmed.

The unit then encounters the "HAS THE SAME ACTUATOR BEEN OPERATED IN THE LAST 0.5 SEC?" decision node 1120. This decision node function is included so that by actuating actuators multiple times, additional functions can be accessed. If the output of the decision node 1120 is "no", the unit is commanded to "SAVE LIGHT LEVEL AS SCENE PRESET" 1130, where a new intensity level is stored for the scene select actuator being programmed.

The program proceeds to "RETURN TO TOP OF MAIN" 1100. If the output of the "HAS THE SAME ACTUATOR BEEN OPERATED IN THE LAST 0.5 SEC?" decision node 1120 is "yes", i.e., multiple actuations of an actuator have occurred within a certain time period, the unit is commanded to "ADD FOUR TO THE SCENE NUMBER" 1122, and "SAVE LIGHT LEVEL AS SCENE PRESET" 1130 and the program proceeds to "RETURN TO TOP OF MAIN" 1000.

If the output of the "TOGGLE?" decision node 1102 is "no" and the output of "RAISE?" decision node 1112 is "no", the program moves to the next major routine and enters the "LOWER?" decision node 1124. A determination is made as to whether the lower power level selector portion 12b has been actuated. If the output from decision node 1124 is "no", no changes are made and the program proceeds to "RETURN TO TOP OF MAIN" 1110. If the output of decision node 1124 is "yes", the program proceeds to the "AT LOW END OR OFF?" decision node 1126. A determination is made as to whether the lamp 114 is at

- 37 -

minimum light intensity or off. If the output from decision node 1120 is "yes", the light intensity can not be decreased further, no changes are made and the program proceeds to "RETURN TO TOP OF MAIN" 1110. If the output from decision node 1126 is "no", the control unit 10 is commanded to "DECREASE LIGHT
5 LEVEL BY ONE STEP" 1128 where the output power of the control unit 10 is decreased and "DETERMINE SCENE" 1118 where once again the unit checks which scene is being programmed.

The program proceeds on to "HAS THE SAME ACTUATOR BEEN
OPERATED IN THE LAST 0.5 SEC?" decision node 1120. If the output from
10 decision node 1120 is "no", the unit is commanded to "SAVE LIGHT LEVEL AS SCENE PRESET" 1130, where the new intensity is stored for the scene select actuator being programmed. The program proceeds to "RETURN TO TOP OF MAIN" 1110. If the output of "HAS THE SAME ACTUATOR BEEN OPERATED
IN THE LAST 0.5 SEC?" decision node 1120 is "yes", the unit is commanded to
15 "ADD FOUR TO THE SCENE NUMBER" 1122, and "SAVE LIGHT LEVEL AS SCENE PRESET" 1130, and then program proceeds to "RETURN TO TOP OF MAIN" 1110.

Turning now to FIG 15 and the "LOWER" routine 1200, the first
decision node encountered is "UNIT ON?" 1202 where a determination is made as
20 to whether the control unit 10 is in the "ON STATE". If the output from the "UNIT ON?" decision node 1202 is "yes", the program proceeds to the "AT LOW END?" decision node 1204 where a determination is made as to whether the lamp 114 is at a minimum light intensity. If the output from the decision node 1204 is "yes", the light intensity can not be decreased any more, no changes are made and the
25 program proceeds to "RETURN TO TOP OF MAIN" 1206. If the output of the "AT LOW END?" decision node 1204 is "no", the program proceeds to the "FADING" decision node 1222. A determination is made as to whether the control unit 10 is in a steady state, or is fading between two different output light intensity levels. If the output from decision node 1222 is "yes", the control unit 10 is fading
30 between two different light intensity levels hence the control unit 10 is commanded to "STOP FADING" 1224 and to "DECREASE LIGHT LEVEL BY ONE STEP" 1212, and the output power of control unit 10 is decreased. The next decision node encountered is the "WAS IT AN IR COMMAND?" 1214.

- 38 -

If the output of the "FADING" decision node 1222 is "no", then the power output from control unit 10 is in a steady state, and the control unit 10 is commanded to "DECREASE LIGHT LEVEL BY ONE STEP" 1212 and the output power of control unit 10 is decreased. The program then proceeds to the "WAS IT AN IR COMMAND?" decision node 1214 where a determination is made as to whether an infra-red signal has been received which caused the program to enter the "LOWER" routine 1200.

If the output from the "WAS IT AN IR COMMAND?" decision node 1214 is "yes", the program proceeds to "UPDATE LEDS" 1216, and then "RETURN TO TOP OF MAIN" 1206. No change is made to any stored preset levels because LOWER commands from the wireless transmitter only affect the current light intensity unless the control unit 10 is in program mode. Further as described below any light intensity levels adjusted by using the user actuatable intensity selection actuator on the control unit 10 are temporary if the locked preset mode is set and are stored if the locked preset mode is not set.

If the output of the "WAS IT AN IR COMMAND?" decision node 1214 is "no", the program proceeds to the "IS LOCKED PRESET MODE SET?" decision node 1208 where a determination is made as to whether a preset light intensity has been stored. If the output from decision node 1208 is "no" and no locked preset has been stored the unit is commanded to "UPDATE PRESET" 1210 where the memory which stores the current value of the unlocked preset has the new intensity level stored in it. The program goes on to "UPDATE LEDS" 1212 where the status of the intensity indicators 14 is updated, and the program proceeds to "RETURN TO TOP OF MAIN" 1206. If the output of the "IS LOCKED PRESET MODE SET?" decision node 1208 is "yes", the unit is commanded to "UPDATE LEDS" 1216, and then "RETURN TO TOP OF MAIN" 1206. No change is made to any stored preset intensity levels.

If the output from of the "UNIT ON?" decision node 1202 is "no", the unit proceeds to the "IN DELAYED OFF PROGRAM MODE?" decision node 1221. A delayed off time can be permanently stored so that every time the user actuates an actuator which causes the control unit 10 to turn off, the unit delays a certain amount of time before turning off. If the control unit 10 is in the mode where a delay to off time is being programmed then the output from decision node

- 39 -

1221 is "yes", and the program proceeds to the "HAS THE LOWER ACTUATOR BEEN HELD FOR 10.0 SEC?" decision node 1226.

5 The permanently stored delay to off time can be cleared by actuating an actuator which causes a "LOWER" 1200 command for an extended period of time, i.e., 10 seconds. If the output from decision node 1226 is "yes", the unit is commanded to "CANCEL DELAYED OFF TIME" 1228, and the program proceeds to "RETURN TO TOP OF MAIN" 1206. If the output from "HAS THE LOWER ACTUATOR BEEN HELD FOR 10.0 SEC?" decision node 1226 is "no", the program proceeds to the "DETERMINE HOW LONG LOWER ACTUATOR HAS BEEN HELD" node 1230 where a determination is made as to how long a "LOWER" 1200 commanding actuator has been actuated. The program continues to "SET DELAYED OFF TO TIME THAT CORRESPONDS TO HOLD TIME" 1232 where the appropriate delay time is stored. The program continues to "FLASH LEDS" 1234 where the indicators are flashed as described above. The program proceeds to "RETURN TO TOP OF MAIN" 1206. The longer the user depresses the "LOWER" commanding actuator, the longer the delayed off time which is stored.

15 If the output from the "IN DELAYED OFF PROGRAM MODE?" decision node 1221 is "no", the unit proceeds to the "HAS THE LOWER BEEN HELD FOR 4.0 SEC?" decision node 1218. To permanently store a delayed off time, the user actuates an actuator which causes a "LOWER" command for an extended period of time, i.e., 4 seconds. If the decision node 1218 is "no", the program proceeds to "RETURN TO TOP OF MAIN" 1206.

20 If the output from decision node 1218 is "yes", the control unit 10 is commanded to "INITIATE DELAYED OFF PROGRAM MODE" 1220, to flash the lowermost indicator 14 as described above, and then "FLASH LEDS" 1234, and then the program proceeds to "RETURN TO TOP OF MAIN" 1206.

25 Turning now to FIG. 16, in the "RAISE" routine 1400, the first decision node encountered is a "UNIT ON?" decision node 1402, where a determination is made as to whether the control unit 10 is in the on state. If the output from the "UNIT ON?" decision node 1402 is "yes", i.e., the control unit 10 is on the program moves to the "AT HIGH END?" decision node 1404 where a determination is made as to whether the lamp 114 is at a maximum light intensity.

- 40 -

If the output from decision node 1404 is "yes", the light intensity cannot be increased any more, so no changes are made and the program proceeds to "RETURN TO TOP OF MAIN" 1420. If the output from decision node 1404 is "no", the routine proceeds to the "FADING?" decision node 1406 where a
5 determination is made as to whether the control unit **10** is in a steady state or is fading between two different output light intensity levels. If the output from decision node 1406 is "yes", the control unit **10** is fading between two different light intensity levels, hence the control unit **10** is commanded to "STOP FADING" 1408 and then to "INCREASE LIGHT LEVEL BY ONE STEP" 1410 where the output power of
10 the control unit **10** is increased. If the output from "FADING" decision node 1406 is "no", the unit is commanded to "INCREASE LIGHT LEVEL BY ONE STEP" 1410 where the output power of the control unit **10** is increased. The program then proceeds to the "WAS IT AN IR COMMAND?" decision node 1412 where a determination is made as to whether an infra-red signal has been received which
15 caused the program to enter the RAISE routine 1400. If the output from decision node 1412 is "yes", the control unit **10** proceeds to "UPDATE LEDS" 1418 and then the program proceeds to "RETURN TO TOP OF MAIN" 1420. No change is made to any stored preset levels because RAISE 1400 routine commands from the wireless transmitter only affect the current light levels unless the control unit
20 **10** is in program mode. If the output from the "WAS IT AN IR COMMAND?" decision node 1412 is "no", the program then proceeds to the "IS LOCKED PRESET MODE SET?" decision node 1414 where a determination is made as to whether a locked preset light intensity level has been stored. If the output from decision node 1414 is "yes", the control unit **10**, proceeds to "UPDATE LEDS" 1418 where the
25 status of intensity indicator **14** is updated and then the program proceeds to RETURN TO TOP OF MAIN 1420. If the output from decision node 1414 is "no", the unit is commanded to "UPDATE PRESET" 1416 where the memory (not shown) which stores the current value of the unlocked preset has the new intensity level stored in the memory, and then goes on to "UPDATE LEDS" 1418. If the output from
30 "UNIT ON?" decision node 1402 is "no", the control unit **10** is commanded to "TURN ON TO LOW END" 1422 where the control unit **10** is turned on, the program goes on to, "INCREASE LIGHT LEVEL BY ONE STEP" 1410 and then to "WAS IT AN IR COMMAND?" decision node 1412.

- 41 -

Turning now to FIG. 17 and the "TOGGLE" routine 1300, the first decision node encountered is "IN LEARN ADDRESS MODE?" 1302 where a determination is made as to whether the control unit **10** is in a mode where it is being labelled with a new address. If the determination is made by the microprocessor

5 **108** that the control unit **10** is being labelled with a new address then the output from decision node 1302 is "yes", and the microprocessor proceeds to "USE NEW ADDRESS AS SIGNAL IDENTIFICATION" 1304 commanding the control unit **10** to store the new address received as its unit address, then "RETURN TO TOP OF MAIN" 1306. As described above, the control unit **10** is capable of receiving

10 a unique addresses via IR signals. This enables the use of a transmitter that has an address selector switch to control a plurality of control units **10** individually. If the output of the "IN LEARN ADDRESS MODE?" decision node 1302 is "no", the program proceeds to the "TOGGLE LAST TIME?" decision node 1330 where a determination is made as to whether control switch actuator **13** is being actuated for

15 more than a transitory period of time. If the output from decision node 1330 is "yes", the program proceeds to the "FADING OFF?" decision node 1332 where a determination is made as to whether the power level at the output of the control unit **10** is decreasing. If the output of the decision node 1332 is "yes", and the power output is decreasing the program proceeds to the "TOGGLE HELD FOR 1/2

20 SECOND?" decision node 1334 where a determination is made as to whether the control switch actuator **13** has been actuated for more than 1/2 second and if so, for how long. If the output of the node is "yes", the control unit **10** is commanded to "DELAY TO OFF WITH DETERMINED DELAY TIME" 1336 where the control unit **10** outputs its current power level for the duration of the delay time

25 corresponding to the length of time the control switch actuator **13** has been actuated, and then decreases the output power level and hence, the light intensity of lamp **114** to zero. The program proceeds to "UPDATE LEDS" 1338 where the indicator **14**, indicating the current intensity level is flashed during the delay time and successively lower indicators are illuminated in turn as the output power level from the control

30 unit **10** is decreased, and then proceeds to "RETURN TO TOP OF MAIN" 1306.

If the output from "TOGGLE LAST TIME?" decision node 1330 is "no", and the control switch actuator **13** is not being actuated for more than a transitory, period of time the program proceeds to the "TOGGLE TAPPED IN LAST 0.5 SEC?" decision node 1318, where a determination is made as to whether

- 42 -

control switch actuator 13 was previously actuated in a transitory manner in the last 0.5 sec. If the output from decision node 1318 is "yes", the program proceeds to the "IS THIS THE THIRD TAP IN 1.0 SECONDS?" decision node 1320 where a determination is made as to whether this is the third actuation of transitory duration in 1.0 sec. If the output from decision node 1320 is "yes", the control unit 10 is commanded to "SAVE THE CURRENT LIGHT LEVEL AS LOCKED PRESET" 1322, wherein the current light intensity level is stored in memory as the LOCKED PRESET light level. The program continues to "REMAIN AT CURRENT LIGHT LEVEL" 1324, the current light intensity level is not changed and then the program proceeds to "BLINK LEDs TWICE" 1326. The indicator 14 indicating the current intensity level is flashed twice at a frequency of 2Hz to indicate that the current light level has been stored and the program proceeds to "SET LOCKED PRESET MODE" 1328 where the microprocessor 108 is updated to reflect that it is in the LOCKED PRESET mode. The program proceeds to "UPDATE LEDS" 1338 where the indicator 14 indicating the current intensity level is illuminated.

If the output from the "IS THIS THE THIRD TAP IN 1.0 SECONDS?" decision node 1320 is "no", the program proceeds to the "IS THIS THE FOURTH TAP IN 1.5 SECONDS?" decision node 1340 where a determination is made as to whether this is the fourth actuation of transitory duration in 1.5 SEC. If the output from decision node 1340 is "no", then it must be the second actuation of transitory duration and the control unit 10 proceeds to "FADE TO FULL WITH FAST FADE" 1346. The light intensity of lamp 114 is increased rapidly to a maximum light intensity, and the program proceeds to "UPDATE LEDS" 1338 where successively higher level indicators are illuminated in turn as the light intensity of lamp 114 increases.

If the output from decision node 1340 is "yes", then this is the fourth actuation of transitory duration in 1.5 sec. The program proceeds to "DISCONTINUE LOCKED PRESET" 1342 where microprocessor 108 is updated to remove the control unit 10 from the LOCKED PRESET mode. The program proceeds to, "BLINK LEDS TWICE" 1344 where the indicator indicating the current intensity level is flashed twice at a frequency of 2Hz and then "UPDATE LEDS" 1338 where the indicator 14 indicating the current intensity level is illuminated.

If the output from "TOGGLE TAPPED IN THE LAST 1/2 SECOND?" decision node 1318 is "no", the program proceeds to the "UNIT ON

- 43 -

OR FADING UP?" node 1308 where a determination is made as to whether the control unit 10 is in the on state, or fading between two intensity levels. If the output from decision node 1308 is "yes", the program proceeds to "DELAYED OFF MODE SET?" decision node 1310. If the output from decision node 1310 is "yes",
5 and a predetermined delay to off time has been stored (see description of set delay routine 1232 in **FIG. 15**), the control unit 10 is commanded to "DELAY TO OFF WITH PROGRAMMED TIME" 1312. The lamp 114 stays at its current intensity level for the stored delay to off time, and then the intensity of lamp 114 decreases to zero. The program proceeds to "RETURN TO TOP OF MAIN" 1306. If the
10 output from "DELAYED OFF MODE SET?" decision node 1310 is "no", the control unit 10 is commanded to "FADE TO OFF" 1314 and the light intensity of lamp 114 is decreased to zero then the program proceeds to "UPDATE LEDS" 1338 when successively lower indicators are illuminated in turn as the light intensity of lamp 114 is decreased.

15 If the output of the "UNIT ON OR FADING UP?" decision node 1308 is "no", the control unit 10 is commanded to "FADE TO PRESET" 1316 where the light intensity of lamp 114 is increased to a preset level. The preset level can be the locked preset level, or the last preset level when the control unit 10 was in the on state. The program proceeds to "UPDATE LEDS" 1338 where
20 successively higher indicators 14 are illuminated in turn as the light intensity of lamp 114 increases.

If the output from the "FADING OFF?" decision node 1332 is "no", the program proceeds to "UPDATE LEDS" 1338 where the status of indicators 14 is updated. If the output of "TOGGLE HELD FOR 1/2 SECOND?" decision node
25 1334 is "no", the program proceeds to "UPDATE LEDS" 1338, and the status of indicators 14 is updated.

Turning now to **FIGS. 18, 19, AND 20** and the "IR SIGNAL" routine 1500, starting with the "CORRECT SIGNAL ADDRESS?" decision node 1550, the control unit 10 determines whether it should respond to IR signals received by
30 first checking to see if the IR signal address matches the unit address. If the addresses do not match the control unit 10 ignores the IR signals. If the output from decision node 1550 is "no", the program proceeds to "RETURN TO TOP OF MAIN" 1564.

- 44 -

If the output from decision node 1550 is "yes", the program proceeds to "IN IR PROGRAM MODE" decision node 1552 where a determination is made as to whether control unit 10 is in the IR PROGRAM MODE. If the output of the node is "no", the program proceeds to a series of decision nodes.

5 The first decision node encountered is "RAISE?" 1528 where a determination is made as to whether the IR signal indicates that an increase power level actuator 23a, 33a, has been actuated or a power level selection actuator 43, 53 has been actuated in its up position. If the output from the "RAISE?" decision node 1528 is "yes", the program proceeds to "GO TO RAISE ROUTINE" 1530
10 which is illustrated in FIG. 16. If the output from decision node 1528 is "no", the program proceeds to the "LOWER?" decision node 1508, where a determination is made as to whether the IR signal indicates that a decrease power level actuator 23b, 33b, has been actuated or a power level selection actuator 43, 53 has been actuated in its down position. If the output from "LOWER?" decision node 1508
15 is "yes", the program proceeds to "GO TO LOWER ROUTINE" 1510 which is illustrated in FIG. 15. If the output from "LOWER?" decision node 1508 is "no", the program proceeds to the "FULL ON?" decision node 1502 where a determination is made as to whether the IR signal indicates that two transitory actuations of a transmitter switch actuator 21 as shown in FIG. 2 have occurred in a short period
20 of time. If the output from decision node 1502 is "yes", the control unit 10 is commanded to "FADE TO FULL ON WITH FAST FADE" 1512 this will cause the light intensity of lamp 114 to increase rapidly to maximum and then "UPDATE LEDS" 1562, where successively higher indicator 14 are illuminated in turn as the light intensity of the lamp 14 increases and then the program proceeds to the TOP
25 OF MAIN 1564.

 If the output from the "FULL ON?" decision node is 1502 is "no", the program proceeds to the "OFF?" decision node 1532 where a determination is made as to whether the IR signal indicates that an off actuator 31b, 41e, 51e has been actuated or transmitter switch actuator 21 has been actuated and the control
30 unit 10 is in the on state. If the output from decision node 1532 is "yes", the control unit 10 is commanded to "FADE TO OFF" 1534 wherein the light intensity of lamp 114 is decreased to zero and then "UPDATE LEDS" 1562 where successively lower indicators 14 are illuminated in turn as the light intensity of lamp 114 is decreased to zero.

- 45 -

If the output of the "OFF?" decision node 1532 is "no", the program proceeds to the "ON TO PRESET?" decision node 1514 where a determination is made as to whether the IR signal indicates that a single actuation of transitory duration of actuator 21 of the basic transmitter shown in FIG. 2 has occurred and the control unit 10 is in the off state. If the output from decision node 1514 is "yes", the control unit 10 is commanded to "FADE TO PRESET" 1516 wherein the light intensity of lamp 114 is increased from zero to a preset intensity level which is either the locked preset intensity level or an unlocked preset intensity level and then "UPDATE LEDS" 1562 where successively higher indicators 14 are illuminated in turn as the light intensity of lamp 114 is increased until the indicator 14 which indicates the preset intensity level is illuminated.

If the output of the "ON TO PRESET?" decision node 1514 is "no", the program proceeds to the "DELAY TO OFF?" decision node 1504 where a determination is made as to whether the IR signal indicates that a transmitter switch actuator 21, or an off actuator 31, 41e, 51e as shown in FIGS 2, 3, 4, and 5 has been actuated for a length of time greater than 0.5 sec. If the output from decision node 1504 is "yes", the control unit 10 is commanded to "DELAY TO OFF WITH DETERMINED DELAY TIME" 1536. The microprocessor 108 determines a delay time from the length of time the actuator 21, 31, 41e, 51e has been actuated, and the control unit 10 causes the lamp 114 to stay at its current light intensity level for the length of the delay time and then the intensity of lamp 114 decreases to zero. The program then proceeds to "UPDATE LEDS" 1562 wherein the indicator 14 indicating the current light intensity level is flashed on and off during the delay time and then successively lower indicators 14 are illuminated in turn as the light intensity of lamp 114 is decreased to zero.

If the output of the "DELAY TO OFF?" decision node 1504 is "no", the program proceeds to the "SCENE COMMAND?" decision node 1518, where a determination is made as to whether the IR signal indicates that one of scene select actuators 31a, 41a-d, 51a-d, or one of the special function actuators 51f-i being used as a scene select actuator on an enhanced wireless transmitter has been actuated. If the output of decision node 1518 is "yes", the program proceeds to "DETERMINE SCENE" 1538 where the particular scene select actuator operated is determined and then the program continues to the "HAS THE SAME SCENE ACTUATOR BEEN OPERATED IN THE LAST 0.5 SEC?" decision node 1540 where a determination

- 46 -

is made as to whether the particular scene select actuator actuated has been previously actuated in the last 0.5 sec. If the output from decision node 1540 is "yes", the program proceeds to "ADD FOUR TO THE SCENE NUMBER" 1542, and the higher numbered stored preset intensity level associated with that particular scene select actuator is used. The program then proceeds to "FADE TO SCENE" 1520 wherein the light intensity of lamp 114 is increased or decreased in value until it is equal to the desired stored preset intensity level associated with that scene select actuator, and previously programmed into the control unit 10 from an enhanced wireless transmitter 30,40, 50. The program proceeds to "UPDATE LEDS" 1562 where the indicator 14 indicating the current light intensity is first illuminated and then successively higher or lower indicators or indicated in turn as the light intensity of lamp 114 is changed until the indicator 14 indicating the preset intensity level is illuminated. If the output of the "HAS THE SAME SCENE ACTUATOR BEEN ACTUATOR IN THE LAST 0.5 SECOND?" decision node 1540 is "no", the program proceeds to "FADE TO SCENE" 1520 without adding four to the scene number and then proceeds to "UPDATE LEDS" 1562 with the same effect on the control unit 10 as described immediately above.

If the output of the "SCENE COMMAND?" decision node 1518 is "no", the program proceeds to the "IR PROGRAM SIGNAL?" decision node 1506 where a determination is made as to whether the IR signal indicates that the appropriate combination of actuators has been actuated on an enhanced transmitter 30, 40, 50 to cause the control unit to enter program mode. If the output of decision node 1506 is "yes", the program proceeds to "HAS PROGRAM SIGNAL BEEN RECEIVED FOR THREE SECONDS?" decision node 1522 where a determination is made as to whether the actuator combination has been actuated for 3 seconds. If the output of decision node 1522 is "yes", the program proceeds to the "CURRENTLY IN PROGRAM MODE?" decision node 1524 where a determination is made as to whether the control unit 10 is currently in the program mode. If the output of decision node 1524 is "yes", the program proceeds to "GO OUT OF IR PROGRAM MODE" 1544 where the control unit 10 exits program mode. The program then proceeds to, "STORE PRESET SCENE LIGHT LEVEL" 1546 where the preset intensity level associated with the last actuator being programmed is stored in memory and then the program proceeds to "STOP FLASHING LEDS" 1548 where the indicators 14 which are being cycled on and off in connection with the

- 47 -

program mode are extinguished and then the program proceeds to "UPDATE LEDS" 1562 where the intensity of indicators 14 is updated to reflect the new condition of the control unit 10 and then the program returns to the TOP OF MAIN 1564.

5 If the output of "CURRENTLY IN PROGRAM MODE?" decision node 1524 is "no", the program proceeds to "ENTER SCENE 1 PROGRAM MODE" 1526. The control unit 10 is commanded to enter program mode and accept signals to adjust the preset light intensity stored for the preset recalled by actuating the first select scene actuator 31a, 41a, 51a. The program then proceeds to "FLASH LEDS" 1560. The indicator 14 is cycled on and off as described above in connection
10 with the description of the programming of a preset light intensity from an enhanced remote control transmitter 30, 40, 50 then the program proceeds to "UPDATE LEDS" 1562 where the intensity of indicators 14 is updated to reflect the new condition of the control unit 10. If the output of the "HAS PROGRAM SIGNAL BEEN RECEIVED FOR THREE SECONDS?" decision node 1522 is "no", the
15 program proceeds to "UPDATE LEDS" 1562. If the output of the "IR PROGRAM SIGNAL?" decision node 1506 is "no", the program proceeds to the "SPECIAL FUNCTION?" decision node 1592 where a determination is made as to whether an IR signal has been received which indicates that a special function actuator 51f-i has been actuated on an enhanced wireless remote 50.

20 If the output of the "SPECIAL FUNCTION" decision node 1592 is "no", the program proceeds to the "LEARN ADDRESS MODE?" decision node 1590 where a determination is made as to whether an IR signal has been received which indicates that the control unit 10 is to be labelled with a new address. If the output of the "LEARN ADDRESS NODE" decision node 1590 is "no", the program
25 proceeds to "RETURN TO TOP OF MAIN" 1564. If the output of the decision node 1590 is "yes", the program proceeds to "SAVE NEW ADDRESS" 1580 where the new address assigned to the control unit 10 is stored in a memory. Then the program proceeds to "RETURN TO TOP OF MAIN" 1564. If the output of the "SPECIAL FUNCTION?" decision node 1592 is "yes" this indicates a special
30 function actuator 51f-i has been actuated on an enhanced wireless remote 50. The program then determines which special function has been selected by proceeding to the "LONG FADE FUNCTION?" decision node 1594 where a determination is made as to whether an IR signal has been received which indicates that the "LONG FADE FUNCTION" has been selected. If the output of the "LONG FADE

- 48 -

FUNCTION" decision node 1594 is "yes", the unit is commanded to "FADE TO OFF WITH DETERMINED FADE TIME" 1596 wherein the light intensity level of lamp 114 is slowly decreased to zero over a time period which is dependant on how long the special function actuator was actuated and then the program proceeds to "FLASH LEDS" 1560, wherein the indicator 14 is cycled on and off as described above in connection with the description of the FADE TO OFF WITH DETERMINED FADE TIME special function. The program then proceeds to "UPDATE LEDS" 1562 where the intensity of indicators 14 is updated to reflect the new condition of the control unit 10. If the output of the "LONG FADE?" decision node 1594 is "no", the program proceeds to the "PREVIOUS LIGHT LEVEL?" decision node 1586 where a determination is made as to whether an IR signal has been received which indicates that the PREVIOUS LIGHT LEVEL special function has been selected. If the output of the "PREVIOUS LIGHT LEVEL" decision node 1586 is "no", the program proceeds to "RETURN TO TOP OF MAIN" 1564. If the output of the "PREVIOUS LIGHT LEVEL" decision node 1586 is "yes", the program proceeds to "RETURN TO PREVIOUS LIGHT LEVEL" 1588 where the control unit 10 is commanded to adjust the light intensity of lamp 114 to be that which it was prior to last being adjusted either by the operation of a scene selection actuator or an increase, or decrease power level selection actuator and then the program proceeds to "UPDATE LEDS" 1562 where the intensity of indicators 14 is updated to reflect the new condition of the control unit 10.

If the output of the "IN IR PROGRAM MODE?" decision node 1552 is "yes", indicating that control unit 10 is in "IR PROGRAM MODE" the program proceeds to the "RAISE?" decision node 1554 where a determination is made as to whether an IR signal has been received which indicates that an increase power level actuator 23a, 33a, has been actuated or a power selector actuator 43, 53 is in its up position. If the output of the "RAISE" decision node 1554 is "yes", the program proceeds to "INCREASE LIGHT LEVEL BY ONE STEP" 1556, where the output power of the control unit 10 is increased and the program then proceeds to "STORE LIGHT LEVEL AS PRESET FOR SCENE" 1558, where the new intensity level is stored for the scene select actuator being programmed and the program proceeds to "FLASH LEDS" 1560, where the indicators 14 are cycled as described above to indicate the scene select actuator being programmed and the current intensity level. The program proceeds to "UPDATE LEDS" 1562, where the intensity of indicators

- 49 -

14 is updated to reflect the new condition of the control unit 10 and the program then proceeds to "RETURN TO TOP OF MAIN" 1564. If the output of the "RAISE?" decision node 1554 is "no", the program proceeds to the "LOWER?" decision node 1566 where a determination is made as to whether an IR signal has
5 been received which indicates that a decrease power level actuator 23b, 33b has been actuated or a power selection actuator 43, 53 is in its down position.

If the output of the "LOWER" decision node 1566 is "yes", the program proceeds to "DECREASE LIGHT LEVEL BY ONE STEP" 1568, where the output power of the control unit 10 is decreased and the program then proceeds
10 to "STORE LIGHT LEVEL AS PRESET FOR SCENE" 1558, "FLASH LED 1560", and then "UPDATE LEDS" 1562 and "RETURN TO TOP OF MAIN" 1564, with the same effects as described immediately above.

If the output of the "LOWER" decision node 1566 is "no", the program proceeds to the "SCENE COMMAND" decision node 1572, where a
15 determination is made as to whether an IR signal has been received which indicates that a scene select actuator 31a, 41a-d, 51a-d has been actuated. If the output of the "SCENE COMMAND" decision node 1572 is "yes", the program proceeds to the "DETERMINE SCENE" node 1574 where a determination is made as to which scene select actuator has been actuated and then the program proceeds to the "HAS
20 THE SAME SCENE ACTUATOR BEEN ACTUATED IN THE LAST 0.5 SEC?" decision node 1576 where a determination is made as to whether the same scene select actuator has been actuated in the last 0.5 seconds. If the output of the "HAS THE SAME SCENE ACTUATOR BEEN ACTUATED IN THE LAST 0.5 SEC" decision node 1576 is "yes", the program proceeds to "ADD FOUR TO THE
25 SCENE NUMBER" 1570, and "FADE TO SCENE" 1578, where the light intensity level of lamp 114 is increased or decreased to the last light intensity level stored for the preset intensity level being programmed. The program then proceeds to "STORE LIGHT LEVEL AS PRESET FOR SCENE" 1558, "FLASH LEDS" 1560 and then "UPDATE LEDS" 1562 and "RETURN TO TOP OF MAIN" 1564 with the same
30 effects as described above.

If the output of the "HAS THE SAME SCENE ACTUATOR BEEN ACTUATED IN THE LAST 0.5 SECOND?" decision node 1576 is "no", the control unit is commanded to "FADE TO SCENE" 1578 without adding four to the scene number, "STORE LIGHT LEVEL AS PRESET FOR SCENE" 1558,

- 50 -

"FLASH LEDS" 1560, "UPDATE LEDS" 1562 and then "RETURN TO TOP OF MAIN" 1564 with the same effects as described above. If the output of the "SCENE COMMAND?" decision node 1572 is "no", the program proceeds to the "OFF?" decision node 1582 where a determination is made as to whether an IR signal has been received which indicates that an off actuator 31b, 41e, 51e has been actuated.

5 If the output of the "OFF" decision node 1582 is "yes", the unit is commanded to "FADE TO OFF" 1584, where the output power of control unit 10 is decreased to zero and the program then proceeds to "STORE LIGHT LEVEL AS PRESET FOR SCENE" 1558, "FLASH LEDS" 1562 "UPDATE LEDS" 1562 and then "RETURN TO TOP OF MAIN" 1564 with the same effects as described above. 10 If the output of the "OFF?" decision node 1582 is "no", the program proceeds to "RETURN TO TOP OF MAIN" 1564.

In an alternate embodiment of the present invention the power control unit 10 includes an infrared lens 70 for receiving infrared signals from the wireless remote control units 20, 30, 40, 50. 15

Referring to FIG. 7, which shows a top plan view of lens 70 the basic principle of operation of the infrared lens 70 is to refract and reflect infrared light through the lens 70 and into a detector 76 which has an infrared receiving surface 78 contained within it which receives the infrared energy and converts it into electrical energy. The lens 70 includes an input surface 71, an output surface 73, and a flat body portion 72 therebetween. The input surface 71 is preferably planar and has a rectangular shape as viewed normal to the input surface 71. Included within the rectangular shape are input surface extension sections 79 which extend beyond the main body portion 72 at opposing ends of the input surface 71. The input surface extension sections 79 enhance the mid angle performance of the lens 70, thereby enabling the lens to capture more of the infrared light that is incident within angles around $\pm 40^\circ$ normal to the input surface 71 as shown in FIG. 8B. 20 25

The lens output surface 73 includes a concave portion 73a which is concave inwardly towards the center of the lens 70. The concave portion 73a refracts infrared light passing through it from body portion 72 onto an input surface 77 of a detector 76, and hence onto receiving surface 78. 30

The body portion 72 has a substantially flat shape with planar top and bottom surfaces, with side surfaces 72a defined by an ellipse 74. The ellipse

- 51 -

74 is defined, in Cartesian coordinates, according to the equation $\frac{x^2}{a^2} + \frac{y^2}{b^2} = 1$, where the ellipse is symmetric with respect to a major axis 74x, and a minor axis 74y such that two arc lengths 74a are the distances from an arbitrary point on the ellipse 74 to the two focal points 74c, 74c'. The two arc lengths 74a from the focal points 74c, 74c' subtend equal angles 74d with the perimeter of the ellipse 74 for any arbitrary point on the ellipse thereby defining the side surfaces 72a of the lens 70. The side surfaces 72a reflect the infrared light entering the body portion 72 from the input surface 71, and direct the reflected light towards the output surface 73 as shown in FIGS. 8A, 8B, and 8C. These figures illustrate infrared light incident to the input surface 71 at 0°, 40°, and 80° respectively, and collectively show how lens 70 captures infrared radiation over a wide angle field of view in the horizontal plane when the lens is installed in actuator 13 as shown in FIG. 9A

The operation of the lens 70 is described with reference to FIG. 7. When a point source of infrared light (not shown) located at focus 74c unidirectionally emits infrared light, then, for all subtended angles 74d (hereinafter α) with angles $\alpha \leq \sin^{-1}(1/n) = \alpha_0$ (Snell's Law: where n is the refractive index of the lens material) the light rays will undergo total internal reflection at the perimeter of the ellipse 74 that define the lens side surfaces 72a. The light is then reflected to the other focus 74c'. As the eccentricity of the ellipse is increased, the subtended angles 74d corresponding to $\alpha \leq \alpha_0$ also increase. Therefore, as the minor axis 74y of the ellipse 74 is decreased, the field of view of the input surface 71 is increased.

In operation, infrared light originates from an external source such as a wireless remote transmitter 20, 30, 40, 50 for a power control unit 10 and enters the input surface 71. In a preferred embodiment of the lens, the input surface 71 has a planar rectangular shape. However, it is understood that the lens can be made in any shape and contour. Preferably, the input surface 71 is a rectangle where the longer dimension is 0.660" and the shorter dimension is .120" as seen from the front of the unit, as shown in FIG. 9A. In addition, the lens 70 is typically constructed from an optical material such as polycarbonate plastic having a refractive index n, which is preferably between 1 and 2, where n is defined as the ratio between the speed of light in a vacuum to the speed of light in the optical material. Preferable Lexan 141 is used having a refractive index $n = 1.586$.

- 52 -

Referring to **FIG 7**, the infrared detector **76** (shown in dashed line) is a infrared receiving diode (photo diode) **78** enclosed in a hemispherical cover **77** typically comprising an infrared transmissive material. A suitable infrared detector is manufactured by Sony and sold under the part number SBX8025-H.

5 In another aspect of the invention the lens **70** is placed on a movable member such as a control switch actuator **13**, and is located as that so that the lens' output surface **73** is adjacent to the input surface **77** of the infrared detector **76**. The infrared detector **76** is located in a fixed position behind the lens **70**. The movable member **13** shown in **FIGs 9A** and **9B** and the lens **70** move in a direction toward
10 and away from the fixed position of the infrared detector **76** and its input surface **77**. Typically, the output surface **73** of the lens **70** is separated from the front surface **77** of detector **76** by 0.080", at the point where it is furthest away from the from surface **77**.

The concave output surface **73** of the lens **70** provides desired optical
15 properties and also conforms generally to the input surface **77** of the detector **76**. This enables lens **70** to be mounted closer to detector **76**.

The above description discloses how to construct two dimensions of a lens **70** with a wide angle of view in a single plane preferably the horizontal plane as lens **70** is installed in control switch actuator **13** and further the operation of lens
20 **70** has been described in two dimensions along **x** and **y** axes.

To construct a lens with a wide angle view in two directions, the above design is used twice in orthogonal directions about the axis **74x** of the lens. The resulting lens is an ellipsoid. The lengths of the **y** axis, **74y**, and the **z** axis (not shown) perpendicular to the light rays entering the lens at zero degrees to the normal
25 are dependent on the shape of the receiving surface **78** in the infrared detector **76**. In the case of a square receiving surface **78** the **y** axis and the **z** axis of the lens are equal, and subsequently the input surface of the **76** lens is circular. Such a lens has equal wide angle performance in all directions in front of the lens. When wide angle performance is desired only along a single plane, the lens nevertheless has to have
30 some thickness. One way to produce such a lens is to slice the ellipsoid top and bottom such that the thickness is preferably approximately equal to the thickness of the receiving surface **78**. The result is an input surface **71** that is substantially a rectangle, with the short edges conforming to arcs of an ellipse. This is substantially

- 53 -

the structure illustrated in **FIGs 7, 9B** where the side surfaces **72a** are portions of ellipses in two directions.

5 The present invention may be embodied in other specific forms without departing from the spirit or essential attributes thereof and, accordingly, reference should be made to the appended claims, rather than to the foregoing specification, as indicating the scope of the invention.

- 54 -

CLAIMS

What is claimed is:

1. Apparatus for remotely controlling power delivered to at least one electrical device comprising:

5 (a) a wireless transmitter having a first transmitter switch for generating and transmitting a first and a second control signal, in response to actuation of said first transmitter switch, and

(b) at least one control unit having a receiver for receiving said first transmitted control signal from said wireless transmitter, said at least one control unit having a control circuit for controlling the power delivered to said at least one electrical device in response to said first control signal,

said second control signal commanding the control unit to store in a memory a preset power level to be delivered to said at least one electrical device

15 2. Apparatus for controlling power delivered to at least one electrical device, comprising:

at least one control unit having a power control circuit and a first control unit switch for generating a first control signal,

said power control circuit controlling the power delivered to said at least one electrical device in response to said first control signal, and

20 said first control unit switch being operative to generate additional control signals to command said at least one control unit to cause the power delivered to said at least one electrical device to decrease from a non-zero power level to a substantially zero power level, and to store a preset power level in a memory.

25 3. Apparatus for controlling power delivered to at least one electrical device, comprising:

at least one control unit having a power control circuit and at least one control unit switch for generating a first, a second and a third control signal,

said power control circuit controlling the power delivered to said at least one electrical device in response to said first control signal,

30 said second control signal commanding the control unit to store a preset power level in a memory, and

said third control signal commanding the control unit to clear said preset power level from said memory.

- 55 -

4. Apparatus for controlling power delivered to at least one electrical device, comprising:

at least one control unit having a power control circuit,

5 a first control unit switch for generating a first control signal in response to actuation of said first control unit switch,

said power control circuit controlling the power delivered to said at least one electrical device in response to said first control signal, and

10 said first control signal commanding said control unit to cause the power delivered to said at least one electrical device to decrease to zero after a first delay time, wherein said first delay time is proportional to a length of time said first control unit switch is actuated.

5. Apparatus for controlling power delivered to at least one electrical device, comprising:

15 at least one control unit having a power control circuit and at least one control unit switch for generating a first, a second and a third control signal,

said power control circuit controlling the power delivered to said at least one electrical device in response to said first control signal,

20 said second control signal commanding said at least one control unit to store in a first memory a duration of delay time, and

said third control signal commanding said at least one control unit to cause the power delivered to said at least one electrical device to decrease from a non-zero power level to a zero power level after said delay time.

6. Apparatus for controlling power delivered to at least one electrical device, comprising:

25 a wireless transmitter having at least one transmitter switch wherein said at least one transmitter switch includes a first and a second transmitter switch for generating and transmitting a first and a second control signal,

30 at least one control unit having a receiver for receiving said first and said second signals from said wireless transmitter, said at least one control unit having addressability and a control circuit for controlling the power delivered to said at least one electrical device,

said first control signal commanding said at least one control unit to be responsive to signals containing one of a plurality of addresses,

- 56 -

said second control signal containing an address component and said at least one control unit responding to said second control signal when said address component of said second control signal is the same as the address assigned to said at least one control unit.

5 7. An apparatus according to claim 2 wherein one of said additional control signals commands said at least one control unit to cause the power delivered to said at least one electrical device to increase from a zero power level to a non-zero power level.

10 8. An apparatus according to claims 1, 2, 3, 4, 5, or 6 wherein said at least one electrical device comprises an electric lamp and said power control circuit for controlling the power delivered to said at least one electrical device, comprises a light intensity control circuit for controlling the light intensity of said electric lamp.

15 9. An apparatus according to claims 2, 3, 4, or 5 wherein actuation of said first control switch commands said at least one control unit to decrease the power supplied to said at least one electrical device from said non-zero power level to a zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be said non-zero power level, and to increase the power supplied to said at least one
20 electrical device from zero to said non-zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be zero.

25 10. An apparatus according to claims 2 or 3, wherein actuation of said first control switch commands said at least one control unit to decrease the power supplied to said at least one electrical device from said non-zero power level to a zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be said non-zero power level, and to increase the power supplied to said at least one
30 electrical device from zero to said non-zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be zero.

wherein said non-zero power level is equal to said stored preset power level when the preset power level is stored in said memory, and when no preset

- 57 -

power level is stored in said memory the non-zero power level state is the last established power level of said at least one electrical device.

11. An apparatus according to claims 2, 3, 4 or 5 wherein two successive actuations of said first control unit switch in a short duration of time commands said at least one control unit to provide maximum power to said at least one electrical device.

12. An apparatus according to claims 2 or 3 wherein three successive actuations of said first control unit switch in a short duration of time commands said at least one control unit to store said preset power level.

13. An apparatus according to claims 2 or 3 wherein four successive actuations of said first control unit switch in a short duration of time commands said at least one control unit to clear said preset power level from said memory.

14. An apparatus according to claims 1, 2, 3, 4, 5, or 6, comprising a second and a third control unit switch wherein an actuation of said second control unit switch commands said at least one control unit to increase the power level to be delivered to said at least one electrical device and wherein actuation of said third control unit switch commands said at least one control unit to decrease the power level to be delivered to said at least one electrical device.

15. An apparatus according to claims 1, 2, or 3 further comprising a second and a third control unit switch wherein an actuation of said second control unit switch commands said at least one control unit to increase the power level to be delivered to said at least one electrical device and wherein actuation of said third control unit switch commands said at least one control unit to decrease the power level to be delivered to said at least one electrical device, wherein said second and third control unit switches are used to set said preset power level to be stored in said memory.

16. An apparatus according to claims 1, 2 or 3 further comprising an indicator which provides an indication that said preset power level has been stored in said memory.

17. An apparatus according to claims 2, 3, 4, or 5 comprising a wireless transmitter having a first transmitter switch, for generating and transmitting at least one transmitted control signal to said at least one control unit,

- 58 -

and a receiver in said at least one control unit for receiving said at least one transmitted control signal.

18. An apparatus according to claims 1 or 17 wherein actuation of said first transmitter switch commands at least one control unit to decrease the power supplied to said at least one electrical device from said non-zero power level to a zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be said non-zero power level, and to increase the power supplied to said at least one electrical device from zero to said non-zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be zero.

19. An apparatus according to claims 1, 2, or 3 wherein actuation of said first transmitter switch commands at least one control unit to decrease the power supplied to said at least one electrical device from said non-zero power level to a zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be said non-zero power level, and to increase the power supplied to said at least one electrical device from zero to said non-zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be zero,

wherein said non-zero power level is equal to said stored preset power level when said preset power level is stored, in said memory and when no power level is stored in said memory, said non-zero power level is the last established power level of said at least one electrical device.

20. An apparatus according to claims 1 or 17 wherein said wireless transmitter transmits infra-red radiation and said receiver receives said infra-red radiation.

21. An apparatus according to claims 1 or 17 wherein two successive actuations of said first transmitter switch in a short duration of time commands said at least one control unit to provide maximum power to said at least one electrical device.

22. An apparatus according to claims 1 or 17 comprising a second and a third transmitter switch wherein actuation of said second transmitter switch commands said at least one control unit to increase the power level to be delivered

- 59 -

to said at least one electrical device and wherein actuation of said third transmitter switch commands said at least one control unit to decrease the power level to be delivered to said at least one electrical device.

23. An apparatus according to claims 1,2, or 3 comprising a
5 second and a third transmitter switch wherein actuation of said second transmitter switch commands said at least one control unit to increase the power level to be delivered to said at least one electrical device and wherein actuation of said third transmitter switch commands said at least one control unit to decrease the power level to be delivered to said at least one electrical device, wherein said second and third
10 transmitter switches are used to set said preset power level to be stored.

24. An apparatus according to claim 1 further comprising at least one additional control unit for controlling the power delivered to additional electrical devices, said additional control units having additional receivers, said control units being responsive to said second control signal to store additional preset power levels
15 to be delivered to respective additional electrical devices.

25. An apparatus according to claim 3 wherein said at least one control unit switch comprises a first, a second and a third control unit switch for generating said first, second and third control signals respectively.

26. An apparatus according to claim 3 wherein said at least one
20 control unit switch comprises a first control unit switch for generating said first control signal and said second control unit switch for generating said second and said third control signal, wherein said second and said third control signal are generated alternately upon successive actuations of said second control unit switch.

27. An apparatus according to claim 4 wherein said at least one
25 control unit further comprises an indicator which provides an indication of said duration of said first delay time.

28. An apparatus according to claim 4 wherein said at least one control unit further comprises an indicator which provides an indication that said at least one control unit has received said first control signal, and said at least one
30 control unit has initiated the first delay time but has not yet reached the end of said duration of said first delay time.

29. An apparatus according to claim 4 wherein duration of said first delay time is linearly proportional to said length of time said control unit switch is closed.

- 60 -

30. An apparatus according to claim 4 wherein actuation of said first control unit switch for a transitory period of time commands said at least one control unit to decrease the power supplied to said at least one electrical device from a non-zero power level to a zero power level without said first delay time, if prior
5 to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be a non-zero power level, and to increase the power supplied to said at least one electrical device from zero to said non-zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be zero.

10 31. An apparatus according to claim 4 wherein said first control unit switch further generates a second and a third control signal,
said second control signal commanding the control unit to store a preset power level in a memory,

15 said third control signal commanding the control unit to clear said preset power level from said memory.

32. An apparatus according to claim 4 further comprising a wireless transmitter having a first transmitter switch for generating and transmitting a first transmitted control signal to said at least one control unit, and a receiver in said at least one control unit for receiving the transmitted control signal, to cause
20 said power delivered to said at least one electrical device to decrease to zero after a second delay time.

33. An apparatus according to claim 32 wherein said second delay time is proportional to a length of time said first transmitter switch is actuated.

25 34. An apparatus according to claim 5 wherein said at least one control unit further comprises an indication that said at least one control unit has received said third control signal, and said at least one control unit has initiated said delay time but has not yet reached the end of said duration of said delay time.

30 35. An apparatus according to claim 5 wherein actuation of said at least one control unit switch for a transitory period of time commands said at least one control unit to decrease the power supplied to said at least one electrical device from a non-zero power level to a zero power level if prior to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be a non-zero power level, and to increase the power supplied to said at least one electrical device from zero to said non-zero power level if prior

- 61 -

to said actuation said power control circuit is controlling said power to be delivered to said at least one electrical device to be zero.

36. An apparatus according to claim 5 wherein said first control unit switch further generates a fourth and a fifth control signal,

5 said fourth control signal commanding said at least one control unit to store a preset power level in a second memory, and

 said fifth control signal commanding said at least one control unit to clear said preset power level from said second memory.

37. An apparatus according to claim 36 comprising a second and
10 a third control unit switch, wherein actuation of said second control unit switch commands said at least one control unit to increase the power level to be delivered to said at least one electrical device, and actuation of said third control unit switch commands said at least one control unit to decrease the power level to be delivered to said at least one electrical device, wherein said at least one control unit further
15 comprises a delay setting switch for setting said duration of said delay time.

38. An apparatus according to claim 37 wherein said delay setting switch is the third control unit switch which is used to set said duration of said delay time when said at least one control unit is controlling the power to be delivered to said at least one electrical device to be zero.

20 39. An apparatus according to claim 5 further comprising a wireless transmitter having

 a first transmitter switch for generating and transmitting a first transmitted control signal to said control unit, and

25 a receiver, in said control unit for receiving said transmitted control signal,

 wherein said first transmitted control signal commands said at least one control unit to cause the power delivered to said at least one electrical device to decrease from said non-zero power level to a zero power level after said duration of said delay time.

30 40. An apparatus according to claim 6 wherein said first transmitter switch is an address selector switch for selecting one of said plurality of addresses to be included in said address component of said second control signal.

41. An apparatus according to claim 40 wherein

- 62 -

said address selector switch is further used for selecting one of said plurality of addresses to be used in said first control signal,

said wireless transmitter further comprising a third transmitter switch, wherein actuation of said third transmitter switch causes said first control signal to be transmitted.

42. An apparatus according to claim 40 wherein one of said plurality of addresses is an all address, and wherein when said all address is included in said address component of said second control signal, all of said at least one control units respond to said second control signal irrespective of the individual addresses which have been assigned to said at least one control units.

43. An apparatus according to claim 6 further comprising a first control unit switch wherein said one of said plurality of addresses is stored in a memory in said at least one control unit when said first control unit switch is actuated within a predetermined period of time after said first control signal is received by said at least one control unit.

44. An apparatus according to claim 43 wherein actuation of said first control unit switch commands said at least one control unit to,

decrease the power supplied to said at least one electrical device from a non-zero power level to a zero power level if prior to said actuation said control circuit is controlling said power to be delivered to said at least one electrical device to be said non-zero power level, and

increase the power supplied to said at least one electrical device from zero to said non-zero power level if prior to said actuation said control circuit is controlling said power to be delivered to said at least one electrical device to be zero, wherein said first control unit switch further generates a third and a fourth control signal,

said third control signal commanding said at least one control unit to store a preset power level in a memory, and

said fourth control signal commanding the control unit to clear said preset power level from said memory.

45. An apparatus according to claim 44 wherein said at least one control unit further comprises a delay setting switch for setting a delay time, wherein actuation of said first control unit switch commands said at least one control unit

- 63 -

to decrease the power supplied to said at least one electrical device from said non-zero power level to said zero power level after a duration of said delay time.

46. An apparatus according to claim 43 wherein
actuation of said first control unit switch commands said at least one
5 control unit to,

decrease the power supplied to said at least one electrical device from
a non-zero power level to a zero power level if prior to said actuation said control
circuit is controlling said power to be delivered to said at least one electrical device
to be said non-zero power level, and

10 to increase the power supplied to said at least one electrical device
from zero to said non-zero power level if prior to said actuation said control circuit
is controlling said power to be delivered to said at least one electrical device to be
zero, and

wherein actuation of said first control unit switch commands said at
15 least one control unit to decrease the power supplied to said at least one electrical
device from said non-zero power level to said zero power level after a delay time,
wherein a duration of said delay time is proportional to a length of time said first
control unit switch is actuated.

47. An apparatus according to claim 6, comprising a fourth and
20 a fifth transmitter switch wherein actuation of said fourth transmitter switch
commands said at least one control unit to increase the power level to be delivered
to said at least one electrical device and wherein actuation of said fifth transmitter
switch commands said at least one control unit to decrease the power level to be
delivered to said at least one electrical device.

25 48. A lens for receiving infrared light, comprising:
an infrared light receiving surface, an infrared light output surface,
and an infrared light transmissive body portion connected therebetween,

said output surface having a concave shape and said body
portion having an external surface substantially conforming to an ellipsoid.

30 49. A lens according to claim 48, wherein said receiving surface
comprises a planar surface having a rectangular shape.

50. A lens according to claim 49, wherein a diameter of said body
portion is smaller than the longer dimension of said rectangle.

51. A lens for receiving infrared light, comprising:

- 64 -

a planar infrared light receiving surface,
an infrared light output surface, and
a flat infrared light transmissive body portion connected
therebetween,

5 said output surface having a shape substantially conforming to an input
surface of an infrared detector, said flat body portion having said external side
surfaces substantially conforming to an ellipse, said side surfaces being laterally
spaced from a longitudinal axis of said body portion and shaped to reflect infrared
light entering said lens input surface and said body portion to said output surface,
10 said output surface directing the infrared light onto said input surface of said infrared
detector, said body portion having a thickness which is less than the distance between
said input and said output surfaces and further less than the distance between said
external side surfaces.

52. An lens according to claim 51, wherein said lens is located
15 on a movable member such that said lens output surface is adjacent to and moves
toward and away from the input surface of said infrared detector.

53. An apparatus for controlling the power delivered to at least
one electrical device, comprising:

(a) a wireless transmitter having a switch for generating and
20 transmitting an infrared control signal, and

(b) at least one control unit having a receiver for receiving said
infrared control signal from said wireless transmitter, said at least one control unit
having a power control circuit for controlling the power delivered to said at least
one electrical device in response to said infrared control signal, and

25 said at least one control unit having an infrared receiving lens, said
lens having an infrared receiving surface, an infrared output surface, and an infrared
transmissive body portion connected therebetween, said output surface having a
convex shape, said body portion having an external surface conforming to an
ellipsoid, formed about a longitudinal axis of the body portion.




30 54. An apparatus according to claim 53, wherein said receiving
surface comprises a planar surface having a rectangular shape.

55. An apparatus according to claim 54, wherein the diameter
of said body portion is smaller than the longest dimension of said rectangle.





- 65 -

56. An apparatus according to claim 53 wherein said at least one control unit comprises a moveable first switch actuator and said infrared receiving lens is located in an opening in said first switch actuator.




1/22

FIG. 1**FIG. 4****FIG. 4A**



2/22

FIG. 2**FIG. 2A****FIG. 2B****FIG. 2C**

3/22

FIG. 3**FIG. 3A****FIG. 3B**

4/22

FIG. 5**FIG. 5A**

5/22




FIG. 6

FIG. 7




7/22




8/22

FIG. 8B



9/22

FIG. 8C



10/22



FIG. 9A**FIG. 9B**

FIG. 10




FIG. 11

12/22





**FIG. 12A**


FIG. 12B

13/22

**FIG. 12C**


14/22

FIG. 13



15/22

FIG. 14



16/22




FIG. 15

FIG. 16



18/22

FIG. 17








FIG. 20

21/22



22/22

FIG. 21



INTERNATIONAL SEARCH REPORT

Inter national Application No
PCI/US 97/03751

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H05B39/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 248 919 A (HANNA ROBERT S ET AL) 28 September 1993 see column 4, line 13 - column 11, line 31; figure 2 ---	1-56
A	US 4 649 323 A (PEARLMAN GORDON W ET AL) 10 March 1987 see the whole document ---	1-56
A	EP 0 471 215 A (ELECTRONIC BALLAST TECHNOLOGY) 19 February 1992 see page 4, line 58 - page 5, line 50; figure 3 -----	1-56

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

16 June 1997

Date of mailing of the international search report

02.07.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

VILLAFUERTE ABR., L

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/03751

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5248919 A	28-09-93	EP 0587878 A	23-03-94
		JP 6508239 T	14-09-94
		US 5399940 A	21-03-95
		WO 9320671 A	14-10-93

US 4649323 A	10-03-87	AU 5600886 A	23-10-86
		BE 904600 A	18-08-86
		CA 1239662 A	26-07-88
		DE 3612264 A	30-10-86
		FR 2580888 A	24-10-86
		GB 2173961 A,B	22-10-86
		JP 61243694 A	29-10-86
		NL 8600894 A	17-11-86
SE 8601588 A	10-11-86		

EP 0471215 A	19-02-92	US 5107184 A	21-04-92
		US 5055746 A	08-10-91
		US 5068576 A	26-11-91
		CA 2049075 A	14-02-92
		JP 4233200 A	21-08-92
